Wood Clear Casting Epoxy Resin Heat Resistance UV Resistant Resin Low Exotherm

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:

• Payment Terms:

- Minimum Order Quantity: 500KG
- Packaging Details: 100g/250g/300g/500g/750g/1kg, 2kg/3kg/5kg/10kg/15kg/20kg/200kg per bottle
 Delivery Time: 5-8 working days

CHINA

CREKOAT

TDS, MSDS DPC-3001

- T/T, Western Union, MoneyGram
- Supply Ability: 300, 000 kg per day



-<u>10</u>0

Product Specification

•	Features:
•	Name:

- Materials:
- State:
- Pot Life:
- Shelf Life:
- Thickness:
- Application:
- Highlight:

No VOC Low Odor			
Deep Pour Epoxy Resin			
Epoxy Resin For Wood			

- Liquid Coating
- 60 Minutes
- 12 Months 5cm~10cm
- Brush, Roller, Stick
- Wood Clear Casting Epoxy Resin, Clear Casting Epoxy Resin Heat Resistance, UV Resistant Resin Low Exotherm





More Images





CREKOAT

High Gloss UV Resistant Clear Casting Deep Pour Epoxy Resin For Wood

Product Descriptions:

Product Name	Casting Epoxy Resin	Casting Epoxy Resin		
Drying time (25°C)	Touch dry≤8 hours / Hard dry≤48 hours	Touch dry≤8 hours / Hard dry≤48 hours		
Viscosity (25°C), cps	Part A 3000-3500, Part B 300			
Solid Content, %	100			
Hardness, shore D	≥90			
Coverage (15kgs Kit)	1"Thick(2.54cm) 6.0 sq.ft			

Quick Details:

Deep Pour Epoxy is a 2-part, extremely clear, deep-cast epoxy. It is ideal for applications where you want a glass-like finish, or thicker pours - you can put this resin up to 50mm (2 inches) deep. This 3:1 mix ratio product was formulated to reduce exotherm (heat build-up) during deep pours, allowing users to pour thicker sections without slowing you down, no need to pour in layers. It is perfect for river tables, resin blanks for lathe turning, filling wide gaps in wood, or any application requiring a depth greater than 9.5mm (3/8 inch). Deep Pour Epoxy can also be layered for projects requiring thicknesses beyond 50mm (2 inches).

Features:

- 1. Odor-free and nontoxic
- 2. Low Viscosity
- 3. U.V. Resistant & Non-Yellowing
- 4. Self-leveling formula
- 5. High-Gloss
- 6. Heat and Impact Resistance

Advantages:

The Deep Pour Epoxy lends itself perfectly to river tables and projects that require a depth of pour up to 50mm in one go. Adding pigments can create stunning creative looks and elevate your project to a stunning work of art. Optically clear with good UV resistance and very low exotherm. Pour up to 50mm in depth in one pour. Use multiple pours to build up higher depth. Due to the low exotherm you are able to pour up to 50mm with confidence. This low viscosity epoxy resin mixture leaves no hole, crack or opening unattended. The slow curing epoxy emits little to no heat and hardens to a durable and solid finish.

CREKOAT Guangdong Crekoat New Materials Co., Ltd.					
C	+8615017402317	info@crekoat.com	epoxyresinfloorcoating.com		
No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China					