

Water Reducible Water Based Floor Coating / Paint Vapor Permeable Semi Gloss

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: WB-3001
Minimum Order Quantity: 500KG

• Packaging Details: Part A: 15 kg in an iron bucket, Part B: 5 kg

in an iron bucket

• Delivery Time: 5-8 working days

• Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 300, 000 kg per day







Product Specification

Features: Very Low VOC ContentName: Water Based Floor Coating


Materials: WB Epoxy Coating
State: Liquid Coating
Pot Life: 30 Minutes
Shelf Life: 12 Months
Thickness: 1mm~3mm

Application: Brush, Roller, Spray

• Highlight: Water Reducible Water Based Floor Coating,

Water Based Floor Coating Vapor Permeable, Water Based Epoxy Paint Semi Gloss

CREKOAT





More Images







Product Description

Low VOC Semi Gloss Water Based Epoxy Coating Chemical Resistant

Product Descriptions:

Product Name	Water Based Epoxy Paint
Drying time (25°C)	Touch dry≤4 hours / Hard dry≤24 hours
Adhesion Strength, Mpa	≥2
Wear resistance (700g / 500r)	≤0.03g
Pencil Hardness (H)	≥3
Coverage (advise 2 coats)	0.2kg/sqm per coat

Quick Details:

Introducing our water-based epoxy range—an effective solution tailored to combat moisture-related floor concerns. Engineered to tackle rising moisture and humidity, these systems boast toughness, water vapor permeability, low VOCs, and minimal odor, providing practical remedies for challenging floor slabs.

Setting itself apart within this range, our system achieves an exceptional A2fl -S1 fire classification, prioritizing safety and compliance without compromising performance.

Available in a diverse color palette, this system offers durability and superior resistance to chemicals, water, and oil-based stains, seamlessly blending reliability with aesthetic appeal for long-lasting, functional floors.

Features:

- 1. Crafted as an effective solution for moisture-related floor issues
- 2. Offers toughness and water vapor permeability
- 3. Low VOC (Volatile Organic Compounds) and exhibit minimal odor
- 4. Environmentally friendly and pleasant application
- 5. Exceptional fire-resistant qualities for added safety
- 6. Variety of Colors: Available in a range of colors

Advantages:

WB EPOXY displays excellent penetrating properties which consolidates the concrete substrate. At the same time, WB EPOXY produces a surface coating/film that will exhibit outstanding water- and chemical-resistance, excellent resistance to acids, solvents, oils, and gasoline and a superior combination of impact, abrasion, and scuff-resistance. Most importantly, WB EPOXY offers the performance characteristics mentioned above in a water-reducible formulation In the past, the physical toughness and resistance properties such as those that WB EPOXY will provide was possible only from solvent-borne products. WB EPOXY should be considered for all interior concrete sealing applications where superior durability is required and solvent odors and flammability are not acceptable.



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China