

## 100% Solids Rock Hard Metallic Epoxy Floor Coating Solvent Based 1mm

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

### Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: MTC-3001
- Minimum Order Quantity: 500KG
- Packaging Details: Part A: 15 kg in an plastic bucket, Part B: 5 kg in an plastic bucket.
- Delivery Time: 5-8 working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 300, 000 kg per day

**CREKOAT**



### Product Specification

- Name: Metallic Epoxy Floor Coating
- Materials: Concrete Epoxy
- State: Liquid Coating
- Mixing Ratio: 3:1 By Weight
- Pot Life: 30 Minutes
- Thickness: 1mm~3mm
- Application: Brush, Roller, Spray
- FeaturesUV Resistant: 100% Solids Solvent Based
- Highlight: **100% Solids Metallic Epoxy Floor Coating, Metallic Epoxy Floor Coating Solvent Based, Rock Hard Floor Coating 1mm**

**CREKOAT**



### More Images

**CREKOAT**



**CREKOAT**



## Product Description

### Rock Hard High Gloss Epoxy Resin Floor Metallic Floor Paint Black

#### Product Descriptions:

Product Name	Self Leveling Epoxy Coating
Drying time (25°C)	Touch dry≤4 hours / Hard dry≤24 hours
Viscosity (25°C), cps	Part A 5000 - 5500, Part B 500-550 cps
Solid Content, %	100
Hardness, shore D	≥85
Coverage (advise 2 coats)	0.5kg/sqm per coat

#### Quick Details:

The metallic coatings need to be applied on black (or on very dark surfaces). Dark surfaces enhance the reflective mirror effect that make the metallic epoxy floor so impressive. The coatings system is composed of several layers:

1. One Epoxy Primer Coat that will seal and penetrate the substrate. Approximate Consumption should be 200 gr/m<sup>2</sup>
2. One Black base epoxy floor coat. Approximate Consumption should be 300 gr/m<sup>2</sup>
3. Application of floor Metallic. Consumption will be approximately 0.5 -1 kg/m<sup>2</sup>. Consumption smaller than this amount can lead to coverage problems. Higher consumption than the recommended amount may lead to metallic effect being distorted.

#### Features:

1. Seamless, easily cleanable surface
2. Resistant to stains and water
3. Durability
4. Self leveling
5. Super gloss finish
6. Amazing and unique results

#### Advantages:

Resin floors are a widely used flooring solution. This system utilizes a mix of materials to create a hardened resin surface. This solution is applied in a liquid form, crafting a seamless flooring system. Resin flooring solutions are incredibly durable and built to last. Some thicker types of resin flooring can even be harder than concrete.

By combining our various resins with specific chemical hardeners, the resulting proprietary systems achieve desired levels of chemical-resistance. Therefore, resin flooring is capable of withstanding years of harsh heavy-duty cleanings, making it a viable option for a wide range of applications. Optional additives can be incorporated into resin flooring to achieve desired effects, such as industrial or decorative aggregates, various pigments, decorative multicolored flakes or natural mica chip blends.



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China