

Antimicrobial Scratch Resistant Floor Coating No Bubbles Black Epoxy Floor Paint

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: MTC-3001
- Minimum Order Quantity: 500KG
- Packaging Details: Part A: 15 kg in an plastic bucket, Part B: 5 kg in an plastic bucket.
- Delivery Time: 5-8 working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 300, 000 kg per day

CREKOAT



Product Specification

- Features: Easy To Use
- Name: Black Epoxy Floor Paint
- State: Liquid Coating
- Mixing Ratio: 3:1 By Weight
- Pot Life: 30 Minutes
- Shelf Life: 12 Months
- Thickness: 1mm~3mm
- Application: Brush, Roller, Spray
- Highlight: Antimicrobial Scratch Resistant Floor Coating, Scratch Resistant Floor Coating No Bubbles, No Bubbles Black Epoxy Floor Paint

CREKOAT




More Images

CREKOAT



CREKOAT



Product Description

Scratch Resistant Black Metallic Epoxy Floor Resin Coating No Bubbles

Product Descriptions:

Product Name	Resin Floor Coating
Drying time (25°C)	Touch dry≤4 hours / Hard dry≤24 hours
Viscosity (25°C), cps	Part A 5000 - 5500, Part B 500-550 cps
Solid Content, %	100
Hardness, shore D	≥85
Coverage (advise 2 coats)	0.5kg/sqm per coat

Quick Details:

Epoxy creates a seamless edge-to-edge surface across an entire floor, conforming to all elements of the floor's topography. There are no cracks, seams, or other breaks in the floor which could allow contaminants such as mold, mildew, or bacteria to thrive. This makes it an excellent choice for any situation where cleanliness is a necessity. As with standard epoxy, metallic epoxy can also be mixed with antimicrobial agents to make it even more resistant to contaminants.

Features:

1. Seamless, easily cleanable surface
2. Resistant to stains and water
3. Durability
4. Self leveling
5. Super gloss finish
6. Amazing and unique results

Advantages:

Resin floors are a widely used flooring solution. This system utilizes a mix of materials to create a hardened resin surface. This solution is applied in a liquid form, crafting a seamless flooring system. Resin flooring solutions are incredibly durable and built to last. Some thicker types of resin flooring can even be harder than concrete. By combining our various resins with specific chemical hardeners, the resulting proprietary systems achieve desired levels of chemical-resistance. Therefore, resin flooring is capable of withstanding years of harsh heavy-duty cleanings, making it a viable option for a wide range of applications. Optional additives can be incorporated into resin flooring to achieve desired effects, such as industrial or decorative aggregates, various pigments, decorative multicolored flakes or natural mica chip blends.



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China