

3mm Marble Metallic Epoxy Floor Coating No Bubbles Quick Curing

Basic Information

. Place of Origin: **CHINA** Brand Name: **CREKOAT** · Certification: TDS, MSDS MTC-3001 Model Number: • Minimum Order Quantity: 500KG

 Packaging Details: Part A: 15 kg in an plastic bucket, Part B: 5

kg in an plastic bucket.

. Delivery Time: 5-8 working days

• Payment Terms: T/T, Western Union, MoneyGram

300, 000 kg per day . Supply Ability:

CREKOAT







Product Specification

Features: No Bubbles

Name: Metallic Epoxy Floor Coating

State: Liquid Coating . Mixing Ratio: 3:1 By Weight · Pot Life: 30 Minutes . Shelf Life: 12 Months Thickness: 1mm~3mm

Application: Brush, Roller, Spray

• Highlight: Marble Metallic Epoxy Floor Coating,

Metallic Epoxy Floor Coating No Bubbles,

3mm Marble Epoxy Floor Coating

CREKOAT







More Images



CREKOAT





Product Description

Quick Curing Marble Epoxy Floor Metallic Pigment Resin Coating

Product Descriptions:

Product Name	Tiles Epoxy Floor Coating
Drying time (25°C)	Touch dry≤4 hours / Hard dry≤24 hours
Viscosity (25°C), cps	Part A 5000 - 5500, Part B 500-550 cps
Solid Content, %	100
Hardness, shore D	≥85
Coverage (advise 2 coats)	0.5kg/sqm per coat

Quick Details:

These stunning floors are created by applying a metallic top coat (sometimes in a contrasting color) over a solid epoxy metallic base coat. The layering of materials produces a spectacular three-dimensional appearance. The epoxy is comprised of a resin and a hardener, mixed together to create a very durable material. The addition of metallic powder creates the unique pearlescence, providing rich color, high-gloss and variable visual effects.

Features:

- 1. Seamless, easily cleanable surface
- 2. Resistant to stains and water
- 3. Durability
- 4. Self leveling
- 5. Super gloss finish
- 6. Amazing and unique results

Advantages:

Resin floors are a widely used flooring solution. This system utilizes a mix of materials to create a hardened resin surface. This solution is applied in a liquid form, crafting a seamless flooring system. Resin flooring solutions are incredibly durable and built to last. Some thicker types of resin flooring can even be harder than concrete.

By combining our various resins with specific chemical hardeners, the resulting proprietary systems achieve desired levels of chemical-resistance. Therefore, resin flooring is capable of withstanding years of harsh heavy-duty cleanings, making it a viable option for a wide range of applications. Optional additives can be incorporated into resin flooring to achieve desired effects, such as industrial or decorative aggregates, various pigments, decorative multicolored flakes or natural mica chip blends.



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China