Stick Two Component Deep Pour Epoxy Resin 100% Solids Ultra Clear

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: DP-3001
Minimum Order Quantity: 500KG

• Packaging Details: 100g/250g/300g/500g/750g/1000g,

2kg/3kg/5kg/10kg/15kg/20kg/200kg per

bottle

Delivery Time: 5-8 working days

• Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 300, 000 kg per day

CREKOAT







Product Specification

• Features: Ultra Clear

Name: Deep Pour Epoxy ResinMaterials: Deep Casting Epoxy Resin

State: Liquid Coating
Mixing Ratio: 3:1 By Weight
Pot Life: 60 Minutes
Thickness: 5cm~10cm

• Application: Brush, Roller, Stick

Highlight: Stick Deep Pour Epoxy Resin,
 Deep Pour Epoxy Resin 100% Solids,

Two Component Epoxy Resin Ultra Clear

CREKOAT







More Images











CREKOAT





Product Description

100% Solids Two Components Liquid Glass Epoxy Resin For Deep Pour

Product Descriptions:

Product Name	Deep Pour Resin Epoxy
Drying time (25°C)	Touch dry≤8 hours / Hard dry≤48 hours
Viscosity (25°C), cps	Part A 3000-3500, Part B 300
Solid Content, %	100
Hardness, shore D	≥90
Coverage (15kgs Kit)	1"Thick(2.54cm) 6.0 sq.ft

Quick Details:

ULTRA DEEP POUR EPOXY CASTING RESIN is a 100% reactive slow-setting epoxy casting system with very low viscosity and high ultraviolet resistance. The DEEP POUR makes it possible to cast river tables, from 60-100 liters, between 2" and 2.5" thick, in a single pour depending on the form and mass while maintaining its transparency and high precision. Its long pot life makes it possible to mix several liters at a time and to pour a large quantity of resin during the production of the river table. We recommend using the Casting Epoxy DEEP POUR for projects between 12-24 inches wide between 2-2.5" thick at 20-22C (70-72F).

Features:

- 1. No VOC's and Low Odor
- 2. Low Viscosity
- 3. U.V. Resistant & Non-Yellowing
- 4. Self Leveling Formula
- 5. High Gloss Durable Finish
- 6. Heat and Impact Resistance

Advantages:

The Deep Pour Epoxy lends itself perfectly to river tables and projects that require a depth of pour up to 50mm in one go. Adding pigments can create stunning creative looks and elevate your project to a stunning work of art. Optically clear with good UV resistance and very low exotherm. Pour up to 50mm in depth in one pour.

Use multiple pours to build up higher depth. Due to the low exotherm you are able to pour up to 50mm with confidence. This low viscosity epoxy resin mixture leaves no hole, crack or opening unattended. The slow curing epoxy emits little to no heat and hardens to a durable and solid finish.



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China