Clear Deep Wood Pour Epoxy Resin UV Resistant Deep Casting Long Lasting

Basic Information

. Place of Origin: **CHINA** Brand Name: **CREKOAT** · Certification: TDS, MSDS Model Number: DP-3001 • Minimum Order Quantity: 500KG

Packaging Details: 100g/250g/300g/500g/750g/1000g,

2kg/3kg/5kg/10kg/15kg/20kg/200kg per

. Delivery Time: 5-8 working days

• Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 300, 000 kg per day









Product Specification

Features: Deep Casting

Name: Deep Pour Epoxy Resin

State: Liquid Coating . Mixing Ratio: 3:1 By Weight · Pot Life: 60 Minutes 12 Months . Shelf Life: 5cm~10cm Thickness:

Application: Brush, Roller, Stick

• Highlight: Clear Deep Pour Epoxy Resin, Deep Pour Epoxy Resin UV Resistant,

Wood Epoxy Resin Deep Casting

CREKOAT







More Images









Product Description

UV Resistant Long Lasting Wood Epoxy Resin Clear Deep Casting

Product Descriptions:

Product Name	Deep Cast Clear Epoxy
Drying time (25°C)	Touch dry≤8 hours / Hard dry≤48 hours
Viscosity (25°C), cps	Part A 3000-3500, Part B 300
Solid Content, %	100
Hardness, shore D	≥90
Coverage (15kgs Kit)	1"Thick(2.54cm) 6.0 sq.ft

Quick Details:

Our casting epoxy resin can be easily mixed with many different types of pigments, ink or powder. You can mix colors to obtain colors and shades you need. Glowing in the dark powder can be of course added and is also available. Usually, for the best glowing effect you can use between 5% - 50%.

Deep pour transparent epoxy resin is ideal for the following applications:

Large and deep pouring areas like river tables or molds

Surface coating for tables, floor, wood, concrete

Perfect for Resin Art

DIY work

Boat repair

For use with fiberglass, carbon fiber

Features:

- 1. No VOC's and Low Odor
- 2. Low Viscosity
- 3. U.V. Resistant & Non-Yellowing
- 4. Self Leveling Formula
- 5. High Gloss Durable Finish
- 6. Heat and Impact Resistance

Advantages:

The Deep Pour Epoxy lends itself perfectly to river tables and projects that require a depth of pour up to 50mm in one go. Adding pigments can create stunning creative looks and elevate your project to a stunning work of art. Optically clear with good UV resistance and very low exotherm. Pour up to 50mm in depth in one pour.

Use multiple pours to build up higher depth. Due to the low exotherm you are able to pour up to 50mm with confidence. This low viscosity epoxy resin mixture leaves no hole, crack or opening unattended. The slow curing epoxy emits little to no heat and hardens to a durable and solid finish.



CREKOAT Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China