

Hardness 2 Part Self Leveling Epoxy Resin Low Viscosity For Casting Molding

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:

• Payment Terms:

Supply Ability:

- Minimum Order Quantity: 500KG
- Packaging Details: 100g/250g/300g/500g/750g/1000g, 2kg/3kg/5kg/10kg/15kg/20kg/200kg per bottle
 Delivery Time: 5-8 working days

CHINA

CREKOAT

TDS, MSDS

DP-3001

- T/T, Western Union, MoneyGram
- 300, 000 kg per day

CREKOAT



Product Specification

- Features:Name:
- Materials:State:
- Otato.
- Mixing Ratio:Shelf Life:
- Thickness:
- Application:
- Highlight:

Eco Friendly
Deep Pour Epoxy Resin
Casting Epoxy

- Liquid Coating
- 3:1 By Weight
- 12 Months
- 5cm~10cm
- Brush, Roller, Stick
 - Hardness Self Leveling Epoxy Resin, Self Leveling Epoxy Resin, 2 Part Epoxy Resin Low Viscosity

CREKOAT



More Images







Self Leveling 2 Part Epoxy Resin For Casting Encapsulation Molding

Product Descriptions:

Product Name	Live Edge Epoxy Resin	
Drying time (25°C)	Touch dry≤8 hours / Hard dry≤48 hours	
Viscosity (25°C), cps	Part A 3000-3500, Part B 300	
Solid Content, %	100	
Hardness, shore D	≥90	
Coverage (15kgs Kit)	1"Thick(2.54cm) 6.0 sq.ft	

Quick Details:

Experience a crystal-clear, high-gloss finish with our premium easy-pour DEEP epoxy resin, perfect for a myriad of applications including epoxy art, encapsulations, and crafting tables. Our 2" - 4" pour epoxy resin kit delivers a flawlessly smooth and rock-hard finish, making it an exceptional choice for river tables and a clear epoxy resin in woodworking projects.

Our VOC-free formula caters to various needs, serving as a countertop epoxy, table-top epoxy, clear casting and coating resin, as well as a high gloss epoxy resin clear coat. Versatile and reliable, our resin ensures an impeccable finish for your creative ventures.

Features:

- 1. No VOC's and Low Odor
- 2. Low Viscosity
- 3. U.V. Resistant & Non-Yellowing
- 4. Self Leveling Formula
- 5. High Gloss Durable Finish
- 6. Heat and Impact Resistance

Advantages:

The Deep Pour Epoxy lends itself perfectly to river tables and projects that require a depth of pour up to 50mm in one go. Adding pigments can create stunning creative looks and elevate your project to a stunning work of art. Optically clear with good UV resistance and very low exotherm. Pour up to 50mm in depth in one pour.

Use multiple pours to build up higher depth. Due to the low exotherm you are able to pour up to 50mm with confidence. This low viscosity epoxy resin mixture leaves no hole, crack or opening unattended. The slow curing epoxy emits little to no heat and hardens to a durable and solid finish.

 CREKOAT
 Guangdong Crekoat New Materials Co., Ltd.

 • +8615017402317
 • info@crekoat.com
 • poxyresinfloorcoating.com
 No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China