

Brush Polyaspartic Polyurea Floor Coating Superior Abrasion Resistance

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: PLS-1001
- Minimum Order Quantity: 500KG
- Packaging Details: Part A: 20 kg in an iron bucket, Part B: 20 kg in an iron bucket.
- Delivery Time: 5-8 working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 300, 000 kg per day

CREKOAT



Product Specification

- Features: Resist Scratches
- Name: Polyaspartic Polyurea Coating
- State: Liquid Coating
- Mixing Ratio: 1:1 By Weight
- Pot Life: 30 Minutes
- Shelf Life: 12 Months
- Thickness: 1mm~3mm
- Application: Brush, Roller, Spray
- Highlight: Brush Polyaspartic Polyurea Floor Coating, Polyaspartic Polyurea Floor Coating, Polyurea Floor Coating

CREKOAT



More Images

CREKOAT



CREKOAT



Product Description

High Durability Polyaspartic Floor Coating Long Lasting Flooring

Product Descriptions:

Product Name	Polyaspartic Flooring
Drying time (25°C)	Touch dry≤2 hours / Hard dry≤12 hours
Viscosity (25°C), cps	Part A 200, Part B 250
Solid Content, %	100
Hardness, shore D	≥50
Coverage (advise 2 coats)	0.3kg/sqm per coat

Quick Details:

Polyaspartics are materials that are considered to be a subset of polyureas. Specifically, the term is usually used to refer to aliphatic polyureas. Polyaspartic floor coatings are typically two-part systems that consist of a resin and a catalyst to facilitate the curing process. While early polyaspartic coatings possessed several limitations, modern formulations are used as alternatives to epoxy and polyurethane coatings.

Features:

1. Fast cure times with excellent adhesion
2. Low Odor, No VOC
3. Superior chemical resistance
4. Superior abrasion resistance
5. Nonyellowing and good gloss retention
6. Easy to mix 1:1 ratio by volume

Advantages:

The cross linking of the Polyaspartic series film in the cure makes it exceptionally tough and durable, making it four times more abrasion resistant than normal epoxy. The chemistry is based upon polyaspartic and much attention has been given to the application and installation attributes in its formulation. As a result, the Polyaspartic clear topcoat is extremely user friendly without having sacrificed the performance of the finished floor coating product. The applications for this product are almost limitless. Polyaspartic is suited for use on high-end residential flooring applications, retail floor settings with high traffic, or food service floor areas where stain resistance and cleanability are paramount.



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China