

Aliphatic Polyaspartic Floor Coating Solid Zero VOC Polymer Concrete Coating

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: PLS-1001
- Minimum Order Quantity: 500KG
- Packaging Details: Part A: 20 kg in an iron bucket, Part B: 20 kg in an iron bucket.
- Delivery Time: 5-8 working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 300, 000 kg per day




Product Specification

- Features: Durable Floor Finishes
- Name: Polymer Concrete Coating
- State: Liquid Coating
- Mixing Ratio: 1:1 By Weight
- Pot Life: 30 Minutes
- Shelf Life: 12 Months
- Thickness: 1mm~3mm
- Application: Brush, Roller, Spray
- Highlight: Aliphatic Polyaspartic Floor Coating, Polyaspartic Floor Coating Solid, Zero VOC Polymer Concrete Coating



More Images



Product Description

Two Component Aliphatic Chemically Cured Polyaspartic Floor Coating

Product Descriptions:

Product Name	Polyaspartic Concrete Coating
Drying time (25°C)	Touch dry≤2 hours / Hard dry≤12 hours
Viscosity (25°C), cps	Part A 200, Part B 250
Solid Content, %	100
Hardness, shore D	≥50
Coverage (advise 2 coats)	0.3kg/sqm per coat

Quick Details:

Polyaspartics provide similar performance as a polyurethane coat but at a higher level. It's also a low-to-zero volatile organic compound (VOC), so the cure time is significantly faster.

Its flexibility, protective strength, and chemical resistance make this a popular choice for:

Garage floors: offer great resistance to oil, grease, and gas.

Industrial applications: Including pipes, pipelines, coatings, sewer linings, tank linings, and water treatment plants.

Automotive refinish and molded parts industry: (due to its fast cure time, even at ambient temperatures)

Features:

1. Fast cure times with excellent adhesion
2. Low Odor, No VOC
3. Superior chemical resistance
4. Superior abrasion resistance
5. Nonyellowing and good gloss retention
6. Easy to mix 1:1 ratio by volume

Advantages:

The cross linking of the Polyaspartic series film in the cure makes it exceptionally tough and durable, making it four times more abrasion resistant than normal epoxy. The chemistry is based upon polyaspartic and much attention has been given to the application and installation attributes in its formulation. As a result, the Polyaspartic clear topcoat is extremely user friendly without having sacrificed the performance of the finished floor coating product. The applications for this product are almost limitless. Polyaspartic is suited for use on high-end residential flooring applications, retail floor settings with high traffic, or food service floor areas where stain resistance and cleanability are paramount.



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China