

Brush Polyaspartic Floor Coating Cleanability Polyurea Clear Top Coat

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: PLS-1001
- Minimum Order Quantity: 500KG
- Packaging Details: Part A: 20 kg in an iron bucket, Part B: 20 kg in an iron bucket.
- Delivery Time: 5-8 working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 300, 000 kg per day

CREKOAT



Product Specification

- Features: High Solid
- Name: Polyaspartic Floor Coating
- Materials: Polyurea Clear
- State: Liquid Coating
- Mixing Ratio: 1:1 By Weight
- Pot Life: 30 Minutes
- Thickness: 1mm~3mm
- Application: Brush, Roller, Spray
- Highlight: Brush Polyaspartic Floor Coating, Polyaspartic Floor Coating Cleanability, Polyurea Clear Top Coat

CREKOAT



More Images

CREKOAT



CREKOAT



Product Description

Two Component Low Odor Polyaspartic Top Coat Sealer Flake Flooring

Product Descriptions:

Product Name	Polyaspartic Flake Floor
Drying time (25°C)	Touch dry≤2 hours / Hard dry≤12 hours
Viscosity (25°C), cps	Part A 200, Part B 250
Solid Content, %	100
Hardness, shore D	≥50
Coverage (advise 2 coats)	0.3kg/sqm per coat

Quick Details:

It has very low or no volatile organic chemicals (VOCs). In other words, it is less time-consuming to cure and requires less downtime. Amazingly, your customers and employees can return to your space in a matter of hours. Superior color and gloss retention and cleanability, Outstanding resistance to abrasion and wear, Impervious to water and deicing salts.

Features:

1. Fast cure times with excellent adhesion
2. Low Odor, No VOC
3. Superior chemical resistance
4. Superior abrasion resistance
5. Nonyellowing and good gloss retention
6. Easy to mix 1:1 ratio by volume

Advantages:

The cross linking of the Polyaspartic series film in the cure makes it exceptionally tough and durable, making it four times more abrasion resistant than normal epoxy. The chemistry is based upon polyaspartic and much attention has been given to the application and installation attributes in its formulation. As a result, the Polyaspartic clear topcoat is extremely user friendly without having sacrificed the performance of the finished floor coating product. The applications for this product are almost limitless. Polyaspartic is suited for use on high-end residential flooring applications, retail floor settings with high traffic, or food service floor areas where stain resistance and cleanability are paramount.



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China