

High Build Aspartic Polyaspartic Floor Coating UV Resistant Non Yellowing

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: PLS-1001
- Minimum Order Quantity: 500KG
- Packaging Details: Part A: 20 kg in an iron bucket, Part B: 20 kg in an iron bucket.
- Delivery Time: 5-8 working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 300, 000 kg per day

CREKOAT



Product Specification


- Features: High Build
- Name: Polyaspartic Floor Coating
- Materials: Aspartic
- State: Liquid Coating
- Mixing Ratio: 1:1 By Weight
- Shelf Life: 12 Months
- Thickness: 1mm~3mm
- Application: Brush, Roller, Spray
- Highlight: High Build Polyaspartic Floor Coating, Polyaspartic Floor Coating UV Resistant, Aspartic Floor Coating

CREKOAT



More Images

CREKOAT



CREKOAT



Product Description

UV Resistant Clear Sealing Coat Polyaspartic Floor Coating Resin

Product Descriptions:

Product Name	Polyaspartic Driveway Coating
Drying time (25°C)	Touch dry≤2 hours / Hard dry≤12 hours
Viscosity (25°C), cps	Part A 200, Part B 250
Solid Content, %	100
Hardness, shore D	≥50
Coverage (advise 2 coats)	0.3kg/sqm per coat

Quick Details:

With fast curing and rapid return to service capabilities, polyaspartic coating products by Crekoat offer industry leading working time, consistency and performance. Crekoat offers a proven history of successful installations with patented formulations that create long-lasting, durable floor finishes, engineered to withstand even the harshest of environments. Our floor polyaspartic coating products are suitable for use in both interior and exterior applications ranging from heavy traffic industrial facilities to decorative commercial spaces and residential homes.

Features:

1. Fast cure times with excellent adhesion
2. Low Odor, No VOC
3. Superior chemical resistance
4. Superior abrasion resistance
5. Nonyellowing and good gloss retention
6. Easy to mix 1:1 ratio by volume

Advantages:

The cross linking of the Polyaspartic series film in the cure makes it exceptionally tough and durable, making it four times more abrasion resistant than normal epoxy. The chemistry is based upon polyaspartic and much attention has been given to the application and installation attributes in its formulation. As a result, the Polyaspartic clear topcoat is extremely user friendly without having sacrificed the performance of the finished floor coating product. The applications for this product are almost limitless. Polyaspartic is suited for use on high-end residential flooring applications, retail floor settings with high traffic, or food service floor areas where stain resistance and cleanability are paramount.



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China