

Minimal Odor Clear Polyurea Concrete Coating Fast Curing Two Part

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: PLS-1001
- Minimum Order Quantity: 500KG
- Packaging Details: Part A: 20 kg in an iron bucket, Part B: 20 kg in an iron bucket.
- Delivery Time: 5-8 working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 300, 000 kg per day

CREKOAT



Product Specification

- Features: Abrasion Resistance
- Name: Polyurea Concrete Coating
- State: Liquid Coating
- Mixing Ratio: 1:1 By Weight
- Pot Life: 30 Minutes
- Shelf Life: 12 Months
- Thickness: 1mm~3mm
- Application: Brush, Roller, Spray
- Highlight: **Minimal Odor Clear Polyurea Coating,
Clear Polyurea Coating,
Polyurea Concrete Coating**

CREKOAT



More Images

CREKOAT



CREKOAT



Product Description

Low VOC Minimal Odor Fast Curing Two Part Polyaspartic Coating

Product Descriptions:

Product Name	Polyurea Polyaspartic Coating
Drying time (25°C)	Touch dry≤2 hours / Hard dry≤12 hours
Viscosity (25°C), cps	Part A 200, Part B 250
Solid Content, %	100
Hardness, shore D	≥50
Coverage (advise 2 coats)	0.3kg/sqm per coat

Quick Details:

Polyaspartic is a low VOC, minimal odor, fast-curing two-part polyaspartic aliphatic polyurea equipped with antimicrobial technology which remains active for the lifetime of the floor coating, even when damaged or worn. It's engineered to retain a low viscosity for longer periods of time, allowing for extended working times and better flow. Designed as a polyaspartic coating for use in hospitals, veterinary clinics, and pharmaceutical facilities, it can be used either as a clear sealer or a topcoat in seamless multi-build systems.

Features:

1. Fast cure times with excellent adhesion
2. Low Odor, No VOC
3. Superior chemical resistance
4. Superior abrasion resistance
5. Nonyellowing and good gloss retention
6. Easy to mix 1:1 ratio by volume

Advantages:

The cross linking of the Polyaspartic series film in the cure makes it exceptionally tough and durable, making it four times more abrasion resistant than normal epoxy. The chemistry is based upon polyaspartic and much attention has been given to the application and installation attributes in its formulation. As a result, the Polyaspartic clear topcoat is extremely user friendly without having sacrificed the performance of the finished floor coating product. The applications for this product are almost limitless. Polyaspartic is suited for use on high-end residential flooring applications, retail floor settings with high traffic, or food service floor areas where stain resistance and cleanability are paramount.



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China