

Tough Polyaspartic Floor Coating / Top Coat Durable Lower Viscosity

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: PLS-1001
- Minimum Order Quantity: 500KG
- Packaging Details: Part A: 20 kg in an iron bucket, Part B: 20 kg in an iron bucket.
- Delivery Time: 5-8 working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 300, 000 kg per day



Product Specification

- Features: Lower Viscosity
- Name: Polyaspartic Top Coat
- State: Liquid Coating
- Mixing Ratio: 1:1 By Weight
- Pot Life: 30 Minutes
- Shelf Life: 12 Months
- Thickness: 1mm~3mm
- Application: Brush, Roller, Spray
- Highlight: Tough Polyaspartic Floor Coating, Polyaspartic Floor Coating Durable, Polyaspartic Top Coat



More Images



Product Description

Tough And Durable Floor Clear Coating Polyaspartic Floor Paint

Product Descriptions:

Product Name	Polyaspartic Floor Coating
Drying time (25°C)	Touch dry≤2 hours / Hard dry≤12 hours
Viscosity (25°C), cps	Part A 200, Part B 250
Solid Content, %	100
Hardness, shore D	≥50
Coverage (advise 2 coats)	0.3kg/sqm per coat

Quick Details:

Polyaspartic is UV stable and is suitable for both interior and exterior applications. It may be tinted with Crekoat Universal Pigments (a line of concentrated colorants compatible with all clear polyaspartic, epoxy and urethane resins). Available colors include: Black, Dark Blue, Tile Red, Light Grey, Medium Grey, Dark Grey, White, Light Beige, Sand Beige, Dark Beige, Light Brown, Safety Yellow and Safety Red. Custom colors are available.

Features:

1. Fast cure times with excellent adhesion
2. Low Odor, No VOC
3. Superior chemical resistance
4. Superior abrasion resistance
5. Nonyellowing and good gloss retention
6. Easy to mix 1:1 ratio by volume

Advantages:

The cross linking of the Polyaspartic series film in the cure makes it exceptionally tough and durable, making it four times more abrasion resistant than normal epoxy. The chemistry is based upon polyaspartic and much attention has been given to the application and installation attributes in its formulation. As a result, the Polyaspartic clear topcoat is extremely user friendly without having sacrificed the performance of the finished floor coating product. The applications for this product are almost limitless. Polyaspartic is suited for use on high-end residential flooring applications, retail floor settings with high traffic, or food service floor areas where stain resistance and cleanability are paramount.



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China