

## Hardness Exterior Epoxy Floor Coating Adhesion Polyaspartic UV Stable Coating


Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

### Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: PLS-1001
- Minimum Order Quantity: 500KG
- Packaging Details: Part A: 20 kg in an iron bucket, Part B: 20 kg in an iron bucket.
- Delivery Time: 5-8 working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 300, 000 kg per day

**CREKOAT**



### Product Specification

- Features: Clear Sealer Finish
- Name: Polyaspartic Floor Coating
- Materials: Polyaspartic Epoxy
- State: Liquid Coating
- Mixing Ratio: 1:1 By Weight
- Shelf Life: 12 Months
- Thickness: 1mm~3mm
- Application: Brush, Roller, Spray
- Highlight: **Hardness Exterior Epoxy Floor Coating, Exterior Epoxy Floor Coating Adhesion, Polyaspartic UV Stable Coating**

**CREKOAT**




### More Images

**CREKOAT**



**CREKOAT**



## Product Description

### UV Stable Polyaspartic Coating For Interior And Exterior Applications

#### Product Descriptions:

Product Name	Polyaspartic Over Epoxy
Drying time (25°C)	Touch dry≤2 hours / Hard dry≤12 hours
Viscosity (25°C), cps	Part A 200, Part B 250
Solid Content, %	100
Hardness, shore D	≥50
Coverage (advise 2 coats)	0.3kg/sqm per coat

#### Quick Details:

Polyaspartic stands as a rapid-curing two-part polyaspartic aliphatic polyurea coating, serving the dual purpose of both decorative enhancement and robust protection. Offering a self-priming feature, it seamlessly applies to diverse substrates such as concrete, metal/steel, and epoxy surfaces.

Our polyaspartic coatings excel in providing outstanding impact, abrasion, and chemical resistance, ensuring durability and longevity. Versatile in application, it serves as an effective clear sealer or as part of seamless multi-build systems, showcasing its adaptability across various protective and aesthetic finishing needs.

#### Features:

1. Fast cure times with excellent adhesion
2. Low Odor, No VOC
3. Superior chemical resistance
4. Superior abrasion resistance
5. Nonyellowing and good gloss retention
6. Easy to mix 1:1 ratio by volume

#### Advantages:

The cross linking of the Polyaspartic series film in the cure makes it exceptionally tough and durable, making it four times more abrasion resistant than normal epoxy. The chemistry is based upon polyaspartic and much attention has been given to the application and installation attributes in its formulation. As a result, the Polyaspartic clear topcoat is extremely user friendly without having sacrificed the performance of the finished floor coating product. The applications for this product are almost limitless. Polyaspartic is suited for use on high-end residential flooring applications, retail floor settings with high traffic, or food service floor areas where stain resistance and cleanability are paramount.



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



[info@crekoat.com](mailto:info@crekoat.com)



[epoxyresinfloorcoating.com](http://epoxyresinfloorcoating.com)

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China