

## Crekoat Two Component High Solids Coating Polyaspartic Nonyellowing TDS

Our Product Introduction

for more products please visit us on [epoxyresinfloorcoating.com](http://epoxyresinfloorcoating.com)

### Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: PLS-1001
- Minimum Order Quantity: 500KG
- Packaging Details: Part A: 20 kg in an iron bucket, Part B: 20 kg in an iron bucket.
- Delivery Time: 5-8 working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 300, 000 kg per day

**CREKOAT**



### Product Specification

- Features: Low VOC
- Name: Polyaspartic Floor Coating
- Materials: Polyaspartic Clear Coat
- Mixing Ratio: 1:1 By Weight
- Pot Life: 30 Minutes
- Shelf Life: 12 Months
- Thickness: 1mm~3mm
- Application: Brush, Roller, Spray
- Highlight: Polyaspartic High Solids Coating,  
High Solids Coating TDS,  
Nonyellowing Two Component Coating

**CREKOAT**



### More Images

**CREKOAT**



**CREKOAT**



## Product Description

### High Solids Two Component Polyaspartic Clear Flooring Topcoat

#### Product Descriptions:

Product Name	Polyaspartic Garage Floor Coating
Drying time (25°C)	Touch dry≤2 hours / Hard dry≤12 hours
Viscosity (25°C), cps	Part A 200, Part B 250
Solid Content, %	100
Hardness, shore D	≥50
Coverage (advise 2 coats)	0.3kg/sqm per coat

#### Quick Details:

The High-Performance Polyaspartic Floor Coating is formulated with cutting edge technology that provides 30-45 minutes of working time allowing your company to reduce the number of installers per job, double your work capacity, improve the quality of your floors, increase revenue, and best of all, provide a beautiful full-bodied, high-build topcoat with only one application. The outstanding feature of this polyaspartic flooring product is the long work time it offers installers, exceptional build, low VOC, excellent chemical resistance, hardness, abrasion resistance, and UV stability. Lastly, as part of our tradition of formulating low VOC coatings, Polyaspartic uses solvents that are shown to not harm the ozone layer.

#### Features:

1. Fast cure times with excellent adhesion
2. Low Odor, No VOC
3. Superior chemical resistance
4. Superior abrasion resistance
5. Nonyellowing and good gloss retention
6. Easy to mix 1:1 ratio by volume

#### Advantages:

The cross linking of the Polyaspartic series film in the cure makes it exceptionally tough and durable, making it four times more abrasion resistant than normal epoxy. The chemistry is based upon polyaspartic and much attention has been given to the application and installation attributes in its formulation. As a result, the Polyaspartic clear topcoat is extremely user friendly without having sacrificed the performance of the finished floor coating product. The applications for this product are almost limitless. Polyaspartic is suited for use on high-end residential flooring applications, retail floor settings with high traffic, or food service floor areas where stain resistance and cleanability are paramount.



Guangdong Crecoat New Materials Co., Ltd.



+8615017402317



[info@crecoat.com](mailto:info@crecoat.com)



[epoxyresinfloorcoating.com](http://epoxyresinfloorcoating.com)

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China