



Liquid Polyaspartic Garage Floor Coating Spray Epoxy Concrete Floor Paint 1mm

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: PLS-1001
- Minimum Order Quantity: 500KG
- Packaging Details: Part A: 20 kg in an iron bucket, Part B: 20 kg in an iron bucket.
- Delivery Time: 5-8 working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 300, 000 kg per day



Product Specification

- Features: UV Stable
- Name: Polyaspartic Floor Coating
- Materials: Polyaspartic Epoxy
- State: Liquid Coating
- Mixing Ratio: 1:1 By Weight
- Pot Life: 30 Minutes
- Thickness: 1mm~3mm
- Application: Brush, Roller, Spray
- Highlight: Liquid Polyaspartic Garage Floor Coating, Polyaspartic Garage Floor Coating, Epoxy Concrete Floor Paint 1mm



More Images



Product Description

Quick Drying High Solid Polyaspartic Epoxy Flake Concrete Floor Paint

Product Descriptions:

Product Name	Polyaspartic Garage Floor Paint
Drying time (25°C)	Touch dry≤2 hours / Hard dry≤12 hours
Viscosity (25°C), cps	Part A 200, Part B 250
Solid Content, %	100
Hardness, shore D	≥50
Coverage (advise 2 coats)	0.3kg/sqm per coat

Quick Details:

Polyaspartic flooring sealer provides a beautiful thick clear film that lays down nicely over most coated concrete floor surfaces. It is widely used over our Roll on Epoxy Flake Flooring System that is designed to be used over concrete floors. The Polyaspartic clear floor coating is also widely used as a protective topcoat over bare concrete floors, stained, commercial, industrial, and decorative concrete floors. The water clear, high-gloss and ultra-high build film of the Polyaspartic provides a beautiful topcoat finish that will look great for years. The chemical backbone of the Polyaspartic is designed to be extremely scratch resistant while also having great chemical resistant properties. The scratch resistance built into the clear topcoat will allow the polyaspartic flooring to maintain its gloss for a longer period of time when compared to other concrete floor coating products.

Features:

1. Fast cure times with excellent adhesion
2. Low Odor, No VOC
3. Superior chemical resistance
4. Superior abrasion resistance
5. Nonyellowing and good gloss retention
6. Easy to mix 1:1 ratio by volume

Advantages:

The cross linking of the Polyaspartic series film in the cure makes it exceptionally tough and durable, making it four times more abrasion resistant than normal epoxy. The chemistry is based upon polyaspartic and much attention has been given to the application and installation attributes in its formulation. As a result, the Polyaspartic clear topcoat is extremely user friendly without having sacrificed the performance of the finished floor coating product. The applications for this product are almost limitless. Polyaspartic is suited for use on high-end residential flooring applications, retail floor settings with high traffic, or food service floor areas where stain resistance and cleanability are paramount.



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China