

## High Solids Polyaspartic Floor Coating / Paint Low Odor 1:1 Mix Ratio

Our Product Introduction

for more products please visit us on [epoxyresinfloorcoating.com](http://epoxyresinfloorcoating.com)

### Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: PLS-1001
- Minimum Order Quantity: 500KG
- Packaging Details: Part A: 20 kg in an iron bucket, Part B: 20 kg in an iron bucket.
- Delivery Time: 5-8 working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 300, 000 kg per day


CREKOAT



### Product Specification

- Features: Rapid Cure
- Name: Polyaspartic Floor Paint
- State: Liquid Coating
- Mixing Ratio: 1:1 By Weight
- Pot Life: 30 Minutes
- Shelf Life: 12 Months
- Thickness: 1mm~3mm
- Application: Brush, Roller, Spray
- Highlight: High Solids Polyaspartic Floor Coating, Polyaspartic Floor Coating Low Odor, Polyaspartic Floor Paint

CREKOAT



### More Images

CREKOAT



CREKOAT



## Product Description

### 1:1 Mix Ratio High Solids Low Odor Polyaspartic Floor Coating

#### Product Descriptions:

Product Name	Polyaspartic Clear Coat
Drying time (25°C)	Touch dry≤2 hours / Hard dry≤12 hours
Viscosity (25°C), cps	Part A 200, Part B 250
Solid Content, %	100
Hardness, shore D	≥50
Coverage (advise 2 coats)	0.3kg/sqm per coat

#### Quick Details:

Polyaspartic can be applied up to 16 mils thick in a single pass to seal floors broadcast with Decorative Chip, decorative quartz and silica sand. It can be applied in a wide range of temperatures and dries to a hard, non-yellowing finish with superior chemical resistance that can be used in both indoor and outdoor applications. Because of the high build that can be achieved in a single pass, and the wide range of application temperatures, installation, and return to service time is greatly reduced over other coatings.

#### Features:

1. Fast cure times with excellent adhesion
2. Low Odor, No VOC
3. Superior chemical resistance
4. Superior abrasion resistance
5. Nonyellowing and good gloss retention
6. Easy to mix 1:1 ratio by volume

#### Advantages:

The cross linking of the Polyaspartic series film in the cure makes it exceptionally tough and durable, making it four times more abrasion resistant than normal epoxy. The chemistry is based upon polyaspartic and much attention has been given to the application and installation attributes in its formulation. As a result, the Polyaspartic clear topcoat is extremely user friendly without having sacrificed the performance of the finished floor coating product. The applications for this product are almost limitless. Polyaspartic is suited for use on high-end residential flooring applications, retail floor settings with high traffic, or food service floor areas where stain resistance and cleanability are paramount.



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



[info@crekoat.com](mailto:info@crekoat.com)



[epoxyresinfloorcoating.com](http://epoxyresinfloorcoating.com)

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China