

Reducible Water Based Floor Coating / Fast Drying Concrete Paint Adhesion TDS

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: WB-3001
- Minimum Order Quantity: 500KG
- Packaging Details: Part A: 15 kg in an iron bucket, Part B: 5 kg in an iron bucket
- Delivery Time: 5-8 working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 300, 000 kg per day

CREKOAT



Product Specification

- Features: Solvent Free
- Name: 30 Minutes
- State: Liquid Coating
- Mixing Ratio: 3:1 By Weight
- Shelf Life: 12 Months
- Thickness: 1mm~3mm
- Application: Brush, Roller, Spray
- Highlight: **Reducible Water Based Floor Coating,
Water Based Floor Coating TDS,
Fast Drying Concrete Paint Adhesion**

CREKOAT



More Images

CREKOAT



CREKOAT



Product Description

Fast Drying Water Based Epoxy Coating For Concrete Flooring

Product Descriptions:

Product Name	Water Based Epoxy Paint
Drying time (25°C)	Touch dry≤4 hours / Hard dry≤24 hours
Adhesion Strength, Mpa	≥2
Wear resistance (700g / 500r)	≤0.03g
Pencil Hardness (H)	≥3
Coverage (advise 2 coats)	0.2kg/sqm per coat

Quick Details:

WB Epoxy Coating is a versatile water-based epoxy resin designed for safe and effortless application. This coating offers similar properties to traditional epoxy resins, with several added benefits, notably its tolerance to application in damp conditions. Its application process is akin to using regular emulsion paint and boasts rapid drying capabilities, forming a durable, easily maintainable coating that acts as an effective waterproof barrier.

Notably non-toxic, this coating exhibits resistance against oils and most mild chemicals. For subsequent coatings, it is advisable to thoroughly degrease and clean the original surface before application.

Features:

1. Fast Application
2. Easy To Use
3. Non Flammable
4. Fire Resistant
5. Low VOC Low Odor
6. Fast Curing

Advantages:

WB EPOXY displays excellent penetrating properties which consolidates the concrete substrate. At the same time, WB EPOXY produces a surface coating/film that will exhibit outstanding water- and chemical-resistance, excellent resistance to acids, solvents, oils, and gasoline and a superior combination of impact, abrasion, and scuff-resistance. Most importantly, WB EPOXY offers the performance characteristics mentioned above in a water-reducible formulation. In the past, the physical toughness and resistance properties such as those that WB EPOXY will provide was possible only from solvent-borne products. WB EPOXY should be considered for all interior concrete sealing applications where superior durability is required and solvent odors and flammability are not acceptable.



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China