

Low Viscosity Hard Wearing Water Based Floor Coating / Paint Solventborne 1mm

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: WB-3001
- Minimum Order Quantity: 500KG
- Packaging Details: Part A: 15 kg in an iron bucket, Part B: 5 kg in an iron bucket
- Delivery Time: 5-8 working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 300, 000 kg per day

CREKOAT



Product Specification

- Features: Slip Resistance
- Name: Hard Wearing Floor Paint
- State: Liquid Coating
- Mixing Ratio: 3:1 By Weight
- Pot Life: 30 Minutes
- Shelf Life: 12 Months
- Thickness: 1mm~3mm
- Application: Brush, Roller, Spray
- Highlight: Low Viscosity Water Based Floor Coating,
Water Based Floor Coating Solventborne,
Hard Wearing Floor Paint 1mm

CREKOAT



More Images

CREKOAT



CREKOAT



Product Description

Non Toxic Low Viscosity Water Based Epoxy Coating Hard Wearing

Product Descriptions:

Product Name	Water Based Epoxy Resin
Drying time (25°C)	Touch dry≤4 hours / Hard dry≤24 hours
Adhesion Strength, Mpa	≥2
Wear resistance (700g / 500r)	≤0.03g
Pencil Hardness (H)	≥3
Coverage (advise 2 coats)	0.2kg/sqm per coat

Quick Details:

Water Based Epoxy Resin is suitable for all applications where concrete or masonry requires waterproofing and protection. It is applied in the same manner as ordinary emulsion paint with the added benefit of application in damp conditions. Once dried Water Based Epoxy leaves a tough, non-toxic, waterproof, easy to clean surface.

A twin-pack water-based epoxy coating suitable for all applications where concrete or masonry requires protection or waterproofing.

Water based epoxy resin will coat over most other finishes but best results are achieved when surfaces are free and clean of other coatings. Any greasy film should be removed prior to application to ensure a sound key. Voids, holes and gaps must be carefully filled.

Features:

1. Fast Application
2. Easy To Use
3. Non Flammable
4. Fire Resistant
5. Low VOC Low Odor
6. Fast Curing

Advantages:

WB EPOXY displays excellent penetrating properties which consolidates the concrete substrate. At the same time, WB EPOXY produces a surface coating/film that will exhibit outstanding water- and chemical-resistance, excellent resistance to acids, solvents, oils, and gasoline and a superior combination of impact, abrasion, and scuff-resistance. Most importantly, WB EPOXY offers the performance characteristics mentioned above in a water-reducible formulation. In the past, the physical toughness and resistance properties such as those that WB EPOXY will provide was possible only from solvent-borne products. WB EPOXY should be considered for all interior concrete sealing applications where superior durability is required and solvent odors and flammability are not acceptable.



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China