

3mm Water Based Epoxy Coating Concrete Floor Paint Solvent Borne Adhesion

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 500KG
- Packaging Details: Part A: 15 kg in an iron bucket, Part B: 5 kg
- Delivery Time:
- Payment Terms:
- Supply Ability:
- 5-8 working days T/T, Western Union, MoneyGram 300, 000 kg per day

CHINA

CREKOAT

TDS, MSDS

in an iron bucket

WB-3001



• Features:

• Name: • State:

• Pot Life:

• Shelf Life:

Thickness:

Application:

• Mixing Ratio:

- Easy To Use Water Based Floor Coating Liquid Coating 3:1 By Weight 30 Minutes
- 12 Months
- 1mm~3mm
- Brush, Roller, Spray
- Highlight:
- 3mm Water Based Epoxy Coating, Water Based Epoxy Coating Solvent Borne, Water Based Concrete Floor Paint Adhesion

CREKOAT

CREKOAT



More Images









Chemical Resistant Water Based Epoxy Coating Concrete Floor Paint

Product Descriptions:

Product Name	Water Based Epoxy Floor Paint	
Drying time (25°C)	Touch dry≤4 hours / Hard dry≤24 hours	
Adhesion Strength, Mpa	≥2	
Wear resistance (700g / 500r)	≤0.03g	
Pencil Hardness (H)	≥3	
Coverage (advise 2 coats)	0.2kg/sqm per coat	

Quick Details:

Waterbased Epoxy is a 2 pack waterbased epoxy coating for internal concrete floors. It is low odour, quick drying and provides a durable low sheen finish which can be tinted to a range of colours using Waterbased Tints. It's also an allergy free coating for house slabs.

Ideal as a coloured coating for garage floors, light traffic warehouse floors, office floors. Once coated. the surface can be sealed with Polyurethane Sealer or Urethane Sealer for a harder wearing surface.

Features:

- 1. Fast Application
- 2. Easy To Use
- 3. Non Flammable
- 4. Fire Resistant
- 5. Low VOC Low Odor
- 6. Excellent Adhesion

Advantages:

WB EPOXY displays excellent penetrating properties which consolidates the concrete substrate. At the same time, WB EPOXY produces a surface coating/film that will exhibit outstanding water- and chemical-resistance, excellent resistance to acids, solvents, oils, and gasoline and a superior combination of impact, abrasion, and scuff-resistance. Most importantly, WB EPOXY offers the performance characteristics mentioned above in a water-reducible formulation In the past, the physical toughness and resistance properties such as those that WB EPOXY will provide was possible only from solvent-borne products. WB EPOXY should be considered for all interior concrete sealing applications where superior durability is required and solvent odors and flammability are not acceptable.

		uangdong Crekoat N	ew Materials Co., Ltd.	
C	+8615017402317	info@crekoat.com	epoxyresinfloorcoating.com	
No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China				