



Waterborne 2 Pack Water Based Floor Coating Recoatable High Build 3mm

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: WB-3001
- Minimum Order Quantity: 500KG
- Packaging Details: Part A: 15 kg in an iron bucket, Part B: 5 kg in an iron bucket
- Delivery Time: 5-8 working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 300, 000 kg per day

CREKOAT



Product Specification

- Features: Water-Based
- Name: Water Based Floor Coating
- State: Liquid Coating
- Mixing Ratio: 3:1 By Weight
- Pot Life: 30 Minutes
- Shelf Life: 12 Months
- Thickness: 1mm~3mm
- Application: Brush, Roller, Spray
- Highlight: Waterborne Water Based Floor Coating, Water Based Floor Coating Recoatable, 2 Pack Floor Coating 3mm

CREKOAT



More Images

CREKOAT



CREKOAT



Product Description

2 Pack High Build Application Water Based Epoxy Floor Coating

Product Descriptions:

Product Name	Waterborne Epoxy Paint
Drying time (25°C)	Touch dry≤4 hours / Hard dry≤24 hours
Adhesion Strength, Mpa	≥2
Wear resistance (700g / 500r)	≤0.03g
Pencil Hardness (H)	≥3
Coverage (advise 2 coats)	0.2kg/sqm per coat

Quick Details:

"Experience the innovation of Crekoat's Two-Pack Epoxy Water-Based Floor Paint, a state-of-the-art semi-gloss coating formulated to deliver a non-flammable, low-odour application, specially crafted for resilient surfaces. Engineered with a focus on floors and primed steelwork, this advanced paint guarantees exceptional durability and impressive resistance against various chemicals.

With an approximate coverage of 5-7 square meters per litre, this paint efficiently covers surfaces, adapting to their nature and porosity. Its rapid drying feature ensures touch dryness in just four hours, allowing for recoating within 24 hours. Moreover, the complete curing process completes within seven days, creating a robust, resilient finish that withstands daily challenges with ease.

Ideal for environments demanding high durability, Crekoat's Two-Pack Epoxy Water-Based Floor Paint is your reliable choice, offering both efficiency and endurance in every application."

Features:

1. Top-tier semi-gloss coating designed for resilient surfaces
2. Chemical resistance, suitable for demanding environments
3. With coverage spanning approximately 5-7 square meters per litre
4. Featuring rapid drying within four hours for touch dryness
5. Delivering a robust and enduring finish
6. Offers reliability and endurance in challenging environments

Advantages:

WB EPOXY displays excellent penetrating properties which consolidates the concrete substrate. At the same time, WB EPOXY produces a surface coating/film that will exhibit outstanding water- and chemical-resistance, excellent resistance to acids, solvents, oils, and gasoline and a superior combination of impact, abrasion, and scuff-resistance. Most importantly, WB EPOXY offers the performance characteristics mentioned above in a water-reducible formulation. In the past, the physical toughness and resistance properties such as those that WB EPOXY will provide was possible only from solvent-borne products. WB EPOXY should be considered for all interior concrete sealing applications where superior durability is required and solvent odors and flammability are not acceptable.



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China