

WB Waterborne Epoxy Floor Coating / Paint Moisture Proof Chemical Resistant


Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: WB-3001
- Minimum Order Quantity: 500KG
- Packaging Details: Part A: 15 kg in an iron bucket, Part B: 5 kg in an iron bucket
- Delivery Time: 5-8 working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 300, 000 kg per day

CREKOAT



Product Specification

- Features: Chemical Resistant
- Name: Water Based Epoxy Floor Coating
- State: Liquid Coating
- Mixing Ratio: 3:1 By Weight
- Pot Life: 30 Minutes
- Shelf Life: 12 Months
- Thickness: 1mm~3mm
- Application: Brush, Roller, Spray
- Highlight: WB Waterborne Epoxy Floor Coating, Waterborne Epoxy Floor Coating, Waterborne Epoxy Floor Paint

CREKOAT



More Images

CREKOAT



CREKOAT



Product Description

Moisture Proof Waterborne Epoxy Coating Concrete Floor Paint

Product Descriptions:

Product Name	Waterborne Epoxy Floor Paint
Drying time (25°C)	Touch dry≤4 hours / Hard dry≤24 hours
Adhesion Strength, Mpa	≥2
Wear resistance (700g / 500r)	≤0.03g
Pencil Hardness (H)	≥3
Coverage (advise 2 coats)	0.2kg/sqm per coat

Quick Details:

Consisting of a two-coat, non-toxic epoxy paint application, this system is designed to excel even in damp conditions. Water-Based Epoxy stands as a water-dispersible coating ideal for waterproofing and safeguarding concrete or masonry surfaces. Its application process mirrors that of conventional paint but offers the added advantage of being applied in damp environments.

Upon curing, Water-Based Epoxy forms a resilient, easy-to-clean, and non-toxic surface that is both waterproof and tough. This feature makes it suitable for a range of settings such as abattoirs, cold rooms, dairies, hospitals, and other areas where minimal odor is crucial. However, it is only recommended for interior surfaces.

Features:

1. Fast Application
2. Easy To Use
3. Non Flammable
4. Fire Resistant
5. Low VOC Low Odor
6. Excellent Adhesion

Advantages:

WB EPOXY displays excellent penetrating properties which consolidates the concrete substrate. At the same time, WB EPOXY produces a surface coating/film that will exhibit outstanding water- and chemical-resistance, excellent resistance to acids, solvents, oils, and gasoline and a superior combination of impact, abrasion, and scuff-resistance. Most importantly, WB EPOXY offers the performance characteristics mentioned above in a water-reducible formulation. In the past, the physical toughness and resistance properties such as those that WB EPOXY will provide was possible only from solvent-borne products. WB EPOXY should be considered for all interior concrete sealing applications where superior durability is required and solvent odors and flammability are not acceptable.



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China