



Glossy Quick Drying Polyurethane Floor Paint 1mm Hardness Water Based

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: PU-7001
- Minimum Order Quantity: 500KG
- Packaging Details: Part A: 20 kg in an iron bucket, Part B: 5 kg in an iron bucket
- Delivery Time: 5-8 working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 300, 000 kg per day



Product Specification

- Features: Water Based
- Name: Polyurethane Floor Paint
- State: Liquid Coating
- Mixing Ratio: 7:1 By Weight
- Pot Life: 60 Minutes
- Shelf Life: 12 Months
- Thickness: 1mm~3mm
- Application: Brush, Roller, Spray
- Highlight: Glossy Polyurethane Floor Paint, Polyurethane Floor Paint 1mm, Quick Drying Floor Paint Hardness



More Images



Product Description

Quick Drying Glossy Water Based Polyurethane Floor Paint

Product Descriptions:

Product Name	Water Based PU Coating
Drying time (25°C)	Touch dry≤4 hours / Hard dry≤14 hours
Impact resistance 500g steel ball (g·cm)	Pass
Wear resistance (700g / 500r)	≤0.03g
Pencil Hardness (H)	≥3
Coverage (advise 2 coats)	0.15kg/sqm per coat

Quick Details:

Designed to give a hard-wearing glossy coating over new or previously painted surfaces.

Is based on alkali resistant pigments and binder.

Is hard-wearing and easy to clean.

Is easy to repaint at any stage of life when re-coating becomes necessary.

Prevent disintegration of cement based floors.

Features:

1. Respectable odor
2. Superior chemical resistance
3. Durability
4. Light stable and gloss retention
5. Fast application
6. UV stability

Advantages:

PU flooring is known to have high resistance to natural chemicals, lactic acids, for instance. This property is what makes PU flooring the best option in the food processing industry because it food grade flooring. However, epoxy flooring does not have resistance towards lactic acids, and it will experience a degree of corrosion and yellowing when coming in contact. Unlike epoxy flooring, polyurethane is known to have higher UV stability. This means the flooring won't turn yellow when exposed to ultraviolet light or sunlight. This gives benefits to users since PU flooring is typically low maintenance once installed.



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China