

Acrylic Latex Traffic Road Marking Paint Hardness Interior And Exterior

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: ARP-001
Minimum Order Quantity: 500KG

• Packaging Details: One Pack: 20 kg in an iron bucket, Custom

packaging is available.

• Delivery Time: 5-8 working days

• Payment Terms: T/T, Western Union, MoneyGram

• Supply Ability: 300, 000 kg per day



Product Specification

• Features: Fast Drying

Name: Traffic Marking Paint
State: Liquid Coating
Mixing Ratio: One Component
Pot Life: 40 Minutes
Shelf Life: 12 Months

• Thickness: 1mm~3mm

• Application: Brush, Roller, Spray

 Highlight: Acrylic Road Marking Paint, Road Marking Paint Hardness,

Latex Traffic Marking Paint

Product Description

Interior And Exterior Acrylic Traffic Paint Road Line Marking

Product Descriptions:

Product Name	Road Line Paint
Drying time (25°C)	Touch dry≤0.2 hours / Hard dry≤6 hours
Adhesion strength, S	≥60
Flexibility, mm	≤0.03
Moh's hardness	≥8
Coverage (advise 2 coats)	0.15kg/sqm per coat

Quick Details:

Our fast-drying, interior and exterior acrylic latex line marking traffic paint is versatile, allowing application with a brush, roller, hand, or automatic line markers. This traffic marking paint efficiently dries to the touch within just 30 minutes, ensuring quick turnaround times for projects. Moreover, for enhanced visibility and safety, traffic beads can be incorporated into the coating while it's still wet, providing light-reflective properties for improved marking. Our line marking paint is specifically formulated for delineating traffic lanes, highways, parking lots, and

This paint not only ensures precise and visible markings but also offers durability and suitability for both indoor and outdoor applications, contributing to enhanced safety and organization in various settings.

Features:

- 1. Good adhesion
- 2. High durability
- 3. Quick drying
- 4. Low VOC
- 5. Fast Application
- 6. Resistant to color fading

Advantages:

Superior environmental impact - as measured by life-cycle analysis, compared to other pavement marking technologies. Enhanced retention of glass beads and greater flexibility - for extended retroreflectivity and improved night-time visibility. Fast-drying properties - with fast-dry-to-nopickup and resistance to early rain showers under a wide range of climatic conditions. Improved wear properties - over various bituminous and concrete road surfaces. Low-VOC formulations - that exceed most road-marking paint regulation.



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China