

## Two Part Metallic Epoxy Floor Coating Skid Resistant High Durability

Our Product Introduction

for more products please visit us on [epoxyresinfloorcoating.com](http://epoxyresinfloorcoating.com)

### Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-MTL2001
- Minimum Order Quantity: 300KG
- Price: US\$4.5-6.5/Kg
- Packaging Details: Bottle/Cartron/Wooden Box
- Delivery Time: 3-7 Working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year



### Product Specification

- Trade Name: Metallic Epoxy Garage Floor
- Traits: High Durability
- Materials: Pure Epoxy Resin
- Key Words: Glass Like Metallic Finish
- Application: Flooring And Counter Top
- Mixing Ratio: 2:1 By Weight
- Pot Life: 30 Minutes
- Shelf Life: 12 Months
- Highlight: **Two Part Metallic Epoxy Floor Coating, Metallic Epoxy Floor Coating Skid Resistant**



### More Images



## Product Description

### Metallic Finishes Two Part Epoxy Resin Floor Coating Skid Resistant

#### Quick Details Of Two Part Epoxy Resin:

Metallic 500 represents a premium-grade, thick build metallic floor coating, delivering an unparalleled depth of color and an exquisite metallic finish available in a diverse array of colors within a single flooring solution. Once meticulously blended using a drill mixer, this coating is gracefully poured onto the floor and evenly spread across the entire surface using a squeegee. For an extra touch, an optional accent color can be gently blended on the floor with a roller. To fortify against heavy foot traffic and harsh chemicals, a final top coat is applied to ensure maximum protection.

Our Metallic 50 and Metallic 100 systems offer monochromatic metallic coatings that prioritize ease of application and cost efficiency. With these systems, simply hand-mix the metallic additive into the clear coat and effortlessly roll it onto the floor surface. For heightened durability, an optional second coat can be applied, enhancing both protection and aesthetics.

#### Features Of Two Part Epoxy Resin:

1. Excellent water & chemical resistance
2. Extraordinary resilience
3. Retards growth of mould, fungus, mildew
4. Easy to apply, clean & maintain
5. Naturally de-foaming with no ripples
6. Tough, high gloss, water resistant coating

#### Advantages Of Two Part Epoxy Resin:

Metallic epoxy floor coating is a low yellowing epoxy resin mixed with metallic pigments. Tiny, shimmering pigments are mixed into the epoxy and poured onto the floor or substrate. When these paints are stirred by a brush or roller, they gather, separate, twist and reflect light at different angles. Eventually, the epoxy hardens and the metallic pigments lock into place, giving them a three-dimensional, swirly appearance. Installation technique is what determines the final look of your floor and is a key part of achieving the desired look.

Metallic epoxy floor coatings are not only aesthetically pleasing, but also offer many other benefits. Metallic epoxy floor coatings can be customized to be extremely durable, low yellowing, seamless, antimicrobial, non-slip and chemical resistant. These floors not only look beautiful, but can meet all your performance needs. They are perfect for waiting rooms, exhibition rooms, restaurants, galleries and more.

#### Product Descriptions Of Two Part Epoxy Resin:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa.s	50-150
Density, g/cm <sup>3</sup>	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D80-85	
Pot Life	30-40mins@25°C	
Curing Time	16-24hrs@25°C, 12-15hrs@35°C 24hrs, Dry Completely	
Max Pour Depth	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages; Warehouses; Airports and hangars; Commercial Use - Shopping malls and boutiques; Hotels; Offices; Showrooms; Restaurants; Hospitals; Schools; Bar Tops, Table Tops. Residential Use – Entrances and hallways; basements; entertainment rooms; bathrooms; kitchens and living rooms;	



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

