



Self Degassing Metallic Epoxy Floor Coating Strong Bond Epoxy Resin And Hardener

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-MTL2001
- Minimum Order Quantity: 300KG
- Price: US\$4.5-6.5/Kg
- Packaging Details: Bottle/Cartron/Wooden Box
- Delivery Time: 3-7 Working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year




Product Specification

- Marketable Name: Epoxy Paint For Concrete
- Special: Self Degassing, Low Odor
- Materials: Epoxy Resin And Hardener
- Key Words: Glass Like Metallic Finish
- Application: Wood, Brick, Ceramic, Concrete
- Mixing Ratio: 2:1 By Weight
- Pot Life: 30 Minutes
- Shelf Life: 12 Months
- Highlight: **Self Degassing Metallic Epoxy Floor Coating, Strong Bond Metallic Epoxy Floor Coating**



More Images



Product Description

Strong Bond Epoxy Resin And Hardener Metallic Epoxy Floor Colors

Quick Details Of Epoxy Resin And Hardener:

With the advent of high-quality metallic pigments and high-performance epoxies, it has become possible to combine colors and designs on floors to stunning effect. From retail stores to restaurants, villas to apartments, from high-end clinics to multi-purpose hotels, customers want to provide visitors with a unique floor-to-floor walking experience. The colors, designs and patterns that can be created with these metallic epoxy materials are simply amazing.

Features Of Epoxy Resin And Hardener:

1. Contains both a UV stabilizer and advanced additive
2. Resistant to yellowing, long lasting
3. Perfect for resin pigment
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Tough, high gloss, water resistant coating

Advantages Of Epoxy Resin And Hardener:

Metallic epoxy floor coating is a low yellowing epoxy resin mixed with metallic pigments. Tiny, shimmering pigments are mixed into the epoxy and poured onto the floor or substrate. When these paints are stirred by a brush or roller, they gather, separate, twist and reflect light at different angles. Eventually, the epoxy hardens and the metallic pigments lock into place, giving them a three-dimensional, swirly appearance. Installation technique is what determines the final look of your floor and is a key part of achieving the desired look.

Metallic epoxy floor coatings are not only aesthetically pleasing, but also offer many other benefits. Metallic epoxy floor coatings can be customized to be extremely durable, low yellowing, seamless, antimicrobial, non-slip and chemical resistant. These floors not only look beautiful, but can meet all your performance needs. They are perfect for waiting rooms, exhibition rooms, restaurants, galleries and more.

Product Descriptions Of Epoxy Resin And Hardener:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa·s	50-150
Density, g/cm ³	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D80-85	
Pot Life	30-40mins@25°C	
Curing Time	16-24hrs@25°C, 12-15hrs@35°C 24hrs, Dry Completely	
Max Pour Depth	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages; Warehouses; Airports and hangars; Commercial Use - Shopping malls and boutiques; Hotels; Offices; Showrooms; Restaurants; Hospitals; Schools; Bar Tops, Table Tops. Residential Use – Entrances and hallways; basements; entertainment rooms; bathrooms; kitchens and living rooms;	



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

