AB Resin System Metallic Epoxy Floor Coating Eco Friendly

Basic Information

. Place of Origin: **CHINA** Brand Name: **CREKOAT** · Certification: TDS, MSDS Model Number: CK-MTL2001 • Minimum Order Quantity: 300KG

• Price: US\$4.5-6.5/Kg

Bottle/Carton/Wooden Box · Packaging Details:

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

. Supply Ability: 1000000 Ton/Year



Product Specification

. Menu Item Name: Concrete Floor Coatings Earmark: **FAST Curing Resin**

· Materials: Epoxy Resin And Hardener Glass Like Metallic Finish . Key Words:

· Application: Wood, Brick, Ceramic, Concrete

Mixing Ratio: 2:1 By Weight Pot Life: 30 Minutes Shelf Life: 12 Months

• Highlight: AB Resin Metallic Epoxy Floor Coating, Metallic Epoxy Floor Coating Eco Friendly

CREKOAT

More Images







Product Description

AB Resin System Eco Friendly Epoxy Resin Metallic Epoxy Coating

Quick Details Of Eco Friendly Epoxy Resin:

Metallic epoxy paints can be used in both residential and commercial environments. In a commercial setting, you can find this flooring in salons, hotel lobbies, retail stores, restaurants, hotels and offices. At home, you can find metal epoxy floors in the living room, kitchen, or basement.

We do not recommend using metal epoxy outdoors as it will discolor when exposed to sunlight.

With over 25 years of experience in the flooring industry, we use our expertise to provide you with the best floor coatings available. We stand behind all of our products with rigorous testing in the harshest industrial and commercial environments.

Features Of Eco Friendly Epoxy Resin:

- 1. 40 minute work time
- 2. Perfect match for all resin pigments
- 3. Self leveling, Self degassing
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Tough and water resistant coating

Advantages Of Eco Friendly Epoxy Resin:

Metallic epoxy floor coating is a low yellowing epoxy resin mixed with metallic pigments. Tiny, shimmering pigments are mixed into the epoxy and poured onto the floor or substrate. When these paints are stirred by a brush or roller, they gather, separate, twist and reflect light at different angles. Eventually, the epoxy hardens and the metallic pigments lock into place, giving them a three-dimensional, swirly appearance. Installation technique is what determines the final look of your floor and is a key part of achieving the desired look.

Metallic epoxy floor coatings are not only aesthetically pleasing, but also offer many other benefits. Metallic epoxy floor coatings can be customized to be extremely durable, low yellowing, seamless, antimicrobial, non-slip and chemical resistant. These floors not only look beautiful, but can meet all your performance needs. They are perfect for waiting rooms, exhibition rooms, restaurants, galleries and more.

Product Descriptions Of Eco Friendly Epoxy Resin:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25ºC	600-800 mPa⋅s	50-150
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D80-85	
Pot Life	30-40mins@25°C	
Curing Time	16-24hrs@25°C, 12-15hrs@35°C	
	24hrs, Dry Completely	
Max Pour Depth	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages; Warehouses; Airports and hangars; Commercial Use - Shopping malls and boutiques; Hotels; Offices; Showrooms; Restaurants; Hospitals; Schools; Bar Tops, Table Tops. Residential Use – Entrances and hallways; basements; entertainment rooms; bathrooms; kitchens and living rooms;	







No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China