

Dries Fast Industrial Garage Floor Epoxy Coating For Concrete Substrate

Basic Information

Place of Origin: CHINABrand Name: CREKOAT

Certification: SGS, TDS, MSDS
Model Number: CK-PT4001
Minimum Order Quantity: 300KG

• Price: US\$3.5-5.5/Kg

Packaging Details:
Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

• Commercial Description: Industrial Polyurethane Floor Coating

Predictable: Perfect For Use In Homes
Materials: Epoxy Resin And Hardener
Key Words: Seamless, High Gloss Finish
Application: Wood, Brick, Ceramic, Concrete

Mixing Ratio: 4:1 By WeightPot Life: 30 MinutesShelf Life: 12 Months

Highlight: Industrial Garage Floor Epoxy Coating,
Dries Fast Garage Floor Epoxy Coating



Product Description

Dries Fast Industrial Garage Floor Epoxy Coating Applied To A Concrete Substrate

Quick Details Of Industrial Garage Floor Epoxy:

In commercial and industrial workplace environments, epoxy resin flooring is a popular flooring choice because epoxy resin has a wide range of ideal properties. However, due to the complexity of the theme of epoxy flooring, there may be some ambiguity in the basic principles and subtle differences of epoxy flooring.

In short, epoxy resin flooring is a synthetic resin flooring system laid on a concrete substrate as a form of protection and decoration. The system can include several layers of thermosetting resin, which are coated, smoothed or poured, and typically applied to a concrete substrate. Once the resin layer is fully cured, the flooring system will form a strong and permanent bond, serving as an impermeable and decorative barrier to protect the substrate.

Features Of Industrial Garage Floor Epoxy:

- 1. Two-part base/top coat system
- 2. Dries fast, low odor and easy to clean
- 3. Odorless, non-flammable
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Tough, high gloss, water resistant coating

Advantages Of Industrial Garage Floor Epoxy:

The chemical and acid resistant epoxy phenolic resin coating kit is a two layer acid and chemical resistant phenolic resin coating system. The characteristic of this system is a layer of reinforced epoxy phenolic varnish primer, followed by a layer of phenolic varnish topcoat. This 2-layer floor coating system is very suitable for use in harsh environments where chemical/acid resistance is crucial. We recommend using it in chemical plants, breweries, wineries, breweries, processing plants, battery storage rooms, chrome plating facilities, and other similar applications. This 2-layer coating is designed for applications that frequently experience splashes/spills of acids, chemicals, and solvents. By allowing the primer to "grab" the concrete and then bonding the topcoat to the primer, a super strong and efficient floor coating is formed, thereby enhancing the strength of the floor. This type of floor can also withstand normal wear and tear, impact drops, pH cleaners, liquids, and any other substances that may enter the floor. It is very easy to clean, just use a mop or wet vacuum cleaner, and quickly make your floor look new.

Product Descriptions Of Industrial Garage Floor Epoxy:

Item	Epoxy Base Material(A)	Epoxy Hardener(B)
Appearance	Liquid	Liquid
Color	Custom Colors	Transparent
Density@25ºC	1.3g/cm3	
Mix Ratio	4:1 by weight	
Hardness	3H	
Pot Life	30-40mins@25°C	
Curing Time	16-24hrs@25°C, 12-15hrs@35°C	
	24hrs, Dry Completely	
Recoat Time	2Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages; Warehouses; Airports and hangars; Commercial Use - Shopping malls and boutiques; Hotels; Offices; Showrooms; Restaurants; Hospitals; Schools; Bar Tops, Table Tops. Residential Use – Entrances and hallways; basements; entertainment rooms; bathrooms; kitchens and living rooms;	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China