

Fast Drying Epoxy Floor Paint Colors Epoxy Flake Coating Non Ambering

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 300KG
- Price:
- Packaging Details:
- Delivery Time:
- 3-7 Working days • Payment Terms:

CHINA

CREKOAT

CK-PT4001

US\$3.5-5.5/Kg

SGS, TDS, MSDS

T/T, Western Union, MoneyGram

Bottle/Carton/Wooden Box

• Supply Ability: 1000000 Ton/Year



Product Specification

- Proprietary Name:
- Fact:
- Materials:
- . Key Words:
- · Application:
- Mixing Ratio:
- Pot Life:
- Shelf Life:
- Highlight:

- Factory Floor Coatings Non-yellowing, Non-ambering Epoxy Resin And Hardener Seamless, High Gloss Finish
- Wood, Brick, Ceramic, Concrete
- 4:1 By Weight
- 30 Minutes
- 12 Months
- - Fast Drying Epoxy Floor Paint, **Epoxy Floor Paint Non Ambering**

CREKOAT



Our Product Introduction

Fast Drying Epoxy Floor Paint Colors Epoxy Flake Coating

Quick Details Of Epoxy Floor Paint Colors:

Epoxy floor coatings are sometimes referred to as epoxy coatings or epoxy floor coatings. The finish usually adopts a uniform single color, and can choose from matte, satin, or glossy finishes. Epoxy floor coatings are usually used in areas with mild to moderate activity, and can also be used in industrial or commercial areas.

Epoxy flake coatings is made by dispersing flakes of different sizes onto a colored epoxy primer, and finally completed with a tough transparent sealant. It produces a decorative floor finish that is easy to clean and has good resistance to pedestrian traffic and chemicals. Epoxy thin film coating is an ideal choice for shops, exhibition halls, restaurants, schools, and many other commercial venues.

Features Of Epoxy Floor Paint Colors:

- 1. Low odor, non-yellowing
- 2. Fast-drying clear coat
- 3. Odorless, non-flammable
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Tough, high gloss, water resistant coating

Advantages Of Epoxy Floor Paint Colors:

The chemical and acid resistant epoxy phenolic resin coating kit is a two layer acid and chemical resistant phenolic resin coating system. The characteristic of this system is a layer of reinforced epoxy phenolic varnish primer, followed by a layer of phenolic varnish topcoat. This 2-layer floor coating system is very suitable for use in harsh environments where chemical/acid resistance is crucial. We recommend using it in chemical plants, breweries, wineries, breweries, processing plants, battery storage rooms, chrome plating facilities, and other similar applications. This 2-layer coating is designed for applications that frequently experience splashes/spills of acids, chemicals, and solvents. By allowing the primer to "grab" the concrete and then bonding the topcoat to the primer, a super strong and efficient floor coating is formed, thereby enhancing the strength of the floor. This type of floor can also withstand normal wear and tear, impact drops, pH cleaners, liquids, and any other substances that may enter the floor. It is very easy to clean, just use a mop or wet vacuum cleaner, and quickly make your floor look new.

Product Descriptions Of Epoxy Floor Paint Colors:

Item	Epoxy Base Material(A)	Epoxy Hardener(B)
Appearance	Liquid	Liquid
Color	Custom Colors	Transparent
Density@25ºC	1.3g/cm3	
Mix Ratio	4:1 by weight	
Hardness	3Н	
Pot Life	30-40mins@25ºC	
Curing Time	16-24hrs@25ºC, 12-15hrs@35ºC	
	24hrs, Dry Completely	
Recoat Time	2Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages; Warehouses; Airports and hangars; Commercial Use - Shopping malls and boutiques; Hotels; Offices; Showrooms; Restaurants; Hospitals; Schools; Bar Tops, Table Tops. Residential Use – Entrances and hallways; basements; entertainment rooms; bathrooms; kitchens and living rooms;	





No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China