CREKOAT

Self Leveling High Gloss White Epoxy Floor Paint Smooth And Seamless **Surface**

Basic Information

. Place of Origin: **CHINA** Brand Name: **CREKOAT**

· Certification: SGS, TDS, MSDS Model Number: CK-PT4001

• Price: US\$3.5-5.5/Kg

Bottle/Carton/Wooden Box Packaging Details:

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

300KG

. Supply Ability: 1000000 Ton/Year

CREKOAT

Product Specification

• Minimum Order Quantity:

• Brand: Best Industrial Floor Paint For Concrete

Essential: Walk On In One Day · Materials: Epoxy Resin And Hardener Seamless, High Gloss Finish . Key Words: · Application: Wood, Brick, Ceramic, Concrete

Mixing Ratio: 4:1 By Weight Pot Life: 30 Minutes Shelf Life: 12 Months

• Highlight: High Gloss White Epoxy Floor Paint, **Self Leveling White Epoxy Floor Paint**

CREKOAT



More Images



Product Description

Self Leveling High Gloss White Epoxy Floor Paint Smooth And Seamless Surface

Quick Details Of High Gloss White Epoxy Floor Paint:

Self leveling (SL) epoxy flooring is a type of flooring that, once poured onto the substrate, has self smoothing properties. Usually, the application range of self leveling systems is between 1 and 3mm, and they are applied in liquid form to achieve rapid installation and achieve smooth and seamless surface treatment. The resin rich formula of epoxy resin SL provides a very sturdy and durable surface treatment for heavy-duty harsh environments. Epoxy resin flooring can be used as a seamless and easy to clean floor surface, with a variety of customizable color choices and various glosses (gloss, satin, matte). Further design options include adding color microchips and metallic pigment additives.

Features Of High Gloss White Epoxy Floor Paint:

- 1. Maximum scratch & stain resistance
- 2. Easy 2-step system
- 3. Odorless, non-flammable
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Tough, high gloss, water resistant coating

Advantages Of High Gloss White Epoxy Floor Paint:

The chemical and acid resistant epoxy phenolic resin coating kit is a two layer acid and chemical resistant phenolic resin coating system. The characteristic of this system is a layer of reinforced epoxy phenolic varnish primer, followed by a layer of phenolic varnish topcoat. This 2-layer floor coating system is very suitable for use in harsh environments where chemical/acid resistance is crucial. We recommend using it in chemical plants, breweries, wineries, breweries, processing plants, battery storage rooms, chrome plating facilities, and other similar applications. This 2-layer coating is designed for applications that frequently experience splashes/spills of acids, chemicals, and solvents. By allowing the primer to "grab" the concrete and then bonding the topcoat to the primer, a super strong and efficient floor coating is formed, thereby enhancing the strength of the floor. This type of floor can also withstand normal wear and tear, impact drops, pH cleaners, liquids, and any other substances that may enter the floor. It is very easy to clean, just use a mop or wet vacuum cleaner, and quickly make your floor look new.

Product Descriptions Of High Gloss White Epoxy Floor Paint:

Item	Epoxy Base Material(A)	Epoxy Hardener(B)
Appearance	Liquid	Liquid
Color	Custom Colors	Transparent
Density@25ºC	1.3g/cm3	
Mix Ratio	4:1 by weight	
Hardness	3H	
Pot Life	30-40mins@25°C	
Curing Time	16-24hrs@25°C, 12-15hrs@35°C	
	24hrs, Dry Completely	
Recoat Time	2Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages; Warehouses; Airports and hangars; Commercial Use - Shopping malls and boutiques; Hotels; Offices; Showrooms; Restaurants; Hospitals; Schools; Bar Tops, Table Tops. Residential Use – Entrances and hallways; basements; entertainment rooms; bathrooms; kitchens and living rooms;	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China