

Heavy Duty White Gloss Epoxy Paint For Food And Beverage Industrial

Basic Information

Place of Origin: CHINABrand Name: CREKOAT

Certification: SGS, TDS, MSDSModel Number: CK-PT4001

Minimum Order Quantity: 300KG
Drice: US\$2.5.5

• Price: US\$3.5-5.5/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

Product Name: Heavy Duty Epoxy Flooring

Nature: Low VOC Formula

Materials: Epoxy Resin And Hardener
Key Words: Seamless, High Gloss Finish
Application: Wood, Brick, Ceramic, Concrete

Mixing Ratio: 4:1 By WeightPot Life: 30 MinutesShelf Life: 12 Months

• Highlight: Heavy Duty White Gloss Epoxy Paint,

Industrial White Gloss Epoxy Paint

CREKOAT



Product Description

Epoxy Mortar White Gloss Epoxy Paint For Food And Beverage Industrial

Quick Details Of White Gloss Epoxy Paint:

Epoxy mortar base is a part of medium to heavy duty flooring systems, typically used as a heavy duty base for laying various resin floors (such as anti slip coatings, self leveling epoxy coatings, etc.). As a thicker type of floor layer, the typical thickness of epoxy mortar layer ranges from 4mm to 6mm. Due to the thickness of the epoxy mortar layer, it is usually necessary to use a trowel to smooth it, and an electric trowel can be used to create a smooth and flat surface.

The epoxy mortar layer has high strength and excellent impact resistance. The epoxy mortar layer can also contain impermeable properties to serve as a moisture-proof membrane. With these properties, epoxy mortar layer is an ideal choice for flooring systems in medium to heavy industrial environments, such as manufacturing, food and beverage processing, etc.

Features Of White Gloss Epoxy Paint:

- 1. Resist to chemicals, water, oil, and grease
- 2. Can be recoated in 24 hours
- 3. Odorless, non-flammable
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Tough, high gloss, water resistant coating

Advantages Of White Gloss Epoxy Paint:

The chemical and acid resistant epoxy phenolic resin coating kit is a two layer acid and chemical resistant phenolic resin coating system. The characteristic of this system is a layer of reinforced epoxy phenolic varnish primer, followed by a layer of phenolic varnish topcoat. This 2-layer floor coating system is very suitable for use in harsh environments where chemical/acid resistance is crucial. We recommend using it in chemical plants, breweries, wineries, breweries, processing plants, battery storage rooms, chrome plating facilities, and other similar applications. This 2-layer coating is designed for applications that frequently experience splashes/spills of acids, chemicals, and solvents. By allowing the primer to "grab" the concrete and then bonding the topcoat to the primer, a super strong and efficient floor coating is formed, thereby enhancing the strength of the floor. This type of floor can also withstand normal wear and tear, impact drops, pH cleaners, liquids, and any other substances that may enter the floor. It is very easy to clean, just use a mop or wet vacuum cleaner, and quickly make your floor look new.

Product Descriptions Of White Gloss Epoxy Paint:

Item	Epoxy Base Material(A)	Epoxy Hardener(B)
Appearance	Liquid	Liquid
Color	Custom Colors	Transparent
Density@25ºC	1.3g/cm3	
Mix Ratio	4:1 by weight	
Hardness	3H	
Pot Life	30-40mins@25°C	
Curing Time	16-24hrs@25°C, 12-15hrs@35°C	
	24hrs, Dry Completely	
Recoat Time	2Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages; Warehouses; Airports and hangars; Commercial Use - Shopping malls and boutiques; Hotels; Offices; Showrooms; Restaurants; Hospitals; Schools; Bar Tops, Table Tops. Residential Use – Entrances and hallways; basements; entertainment rooms; bathrooms; kitchens and living rooms;	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China