

Flake Decorative Concrete Floor Coating Epoxy Varnish Intermediate Coating

Basic Information

• Minimum Order Quantity:

Place of Origin: CHINABrand Name: CREKOAT

Certification: SGS, TDS, MSDSModel Number: CK-PT4001

• Price: US\$3.5-5.5/Kg

Packaging Details:
Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

300KG

Supply Ability: 1000000 Ton/Year



Product Specification

Operating Name: Industrial Flooring Epoxy Coating

• Exemplary: Resistant To Abrasions And Chemicals

Materials: Epoxy Resin And Hardener
Key Words: Seamless, High Gloss Finish
Application: Wood, Brick, Ceramic, Concrete

Mixing Ratio: 4:1 By WeightPot Life: 30 MinutesShelf Life: 12 Months

• Highlight: Flake Decorative Concrete Floor Coating,

Epoxy Varnish Concrete Floor Coating

CREKOAT



More Images



Product Description

Flake Decorative Concrete Floor Coating Epoxy Varnish Intermediate Coating

Quick Details Of Decorative Concrete Floor Coating:

Industrial epoxy floor coatings can be used to form low or high structural finishes. It is often used as an economical option to create intermediate constructions on flake flooring systems, making it easy to create smooth and uniform finishes. Industrial epoxy floor coatings can also be used to provide more medium to high thickness finishes than other epoxy systems, decorative floor coverings, and various other floor styles. Epoxy varnish is widely accepted as an intermediate coating on flake systems to provide a smooth surface through coating applicators. When using in this way, make sure to terminate the epoxy resin at the edge of the door. Do not touch the outer surface, otherwise it will turn yellow.

Features Of Decorative Concrete Floor Coating:

- 1. Water-based, environment-friendly
- 2. Non-yellowing and highly resistant
- 3. Odorless, Non-flammable
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Tough, high gloss, water resistant coating

Advantages Of Decorative Concrete Floor Coating:

The chemical and acid resistant epoxy phenolic resin coating kit is a two layer acid and chemical resistant phenolic resin coating system. The characteristic of this system is a layer of reinforced epoxy phenolic varnish primer, followed by a layer of phenolic varnish topcoat. This 2-layer floor coating system is very suitable for use in harsh environments where chemical/acid resistance is crucial. We recommend using it in chemical plants, breweries, wineries, breweries, processing plants, battery storage rooms, chrome plating facilities, and other similar applications. This 2-layer coating is designed for applications that frequently experience splashes/spills of acids, chemicals, and solvents. By allowing the primer to "grab" the concrete and then bonding the topcoat to the primer, a super strong and efficient floor coating is formed, thereby enhancing the strength of the floor. This type of floor can also withstand normal wear and tear, impact drops, pH cleaners, liquids, and any other substances that may enter the floor. It is very easy to clean, just use a mop or wet vacuum cleaner, and quickly make your floor look new.

Product Descriptions Of Decorative Concrete Floor Coating:

Item	Epoxy Base Material(A)	Epoxy Hardener(B)
Appearance	Liquid	Liquid
Color	Custom Colors	Transparent
Density@25ºC	1.3g/cm3	
Mix Ratio	4:1 by weight	
Hardness	3H	
Pot Life	30-40mins@25°C	
Curing Time	16-24hrs@25°C, 12-15hrs@35°C	
	24hrs, Dry Completely	
Recoat Time	2Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages; Warehouses; Airports and hangars; Commercial Use - Shopping malls and boutiques; Hotels; Offices; Showrooms; Restaurants; Hospitals; Schools; Bar Tops, Table Tops. Residential Use – Entrances and hallways; basements; entertainment rooms; bathrooms; kitchens and living rooms;	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China