• Price: US\$4.5-6.5/Kg

Packaging Details:
Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

300KG

Supply Ability: 1000000 Ton/Year

CREKOAT



Product Specification

• Minimum Order Quantity:

Sales Name: Epoxy Flakes

Normal: Interior Or Exterior Use
Materials: Epoxy Resin And Hardener
Key Words: Glass Like Metallic Finish

Mixing Ratio: 2:1 By WeightPot Life: 30 MinutesShelf Life: 12 Months

Highlight: Safe Flakes Epoxy Resin Floor Coating,
Custom Color Epoxy Resin Floor Coating

CREKOAT



More Images

· Application:





Wood, Brick, Ceramic, Concrete



Our Product Introduction

Product Description

Safe Flakes Epoxy Resin Floor Coating With Custom Colors And Textures

Quick Details Of Epoxy Resin Floor Coating:

Resin flooring systems have excellent chemical resistance and wear resistance compared to prefabricated flooring. Enhance your high-performance flooring environment by adding custom colors and textures to complement any decor. The Flakes resin flooring system provides a cost-effective alternative to prefabricated flooring. Safe Flakes resin flooring media provides orange peel texture, improving slip resistance and safety.

The resin flooring system does not contain wax and is economical to maintain with soap and water. Resin flooring provides a seamless wall to wall aesthetic that does not collect dirt, moisture, or bacteria. After years of use, effectively revitalize your resin flooring system by polishing the surface and applying new topcoats.

Features Of Epoxy Resin Floor Coating:

- 1. High traction coefficient
- 2. Wide assortment of custom finishes
- 3. Odorless, non-flammable
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Tough, high gloss, water resistant

Advantages Of Epoxy Resin Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Resin Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25ºC	600-800 mPa⋅s	50-150
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	16-24hrs@25°C, 12-15hrs@35°C	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages; Warehouses; Airports and hangars;	
	Commercial Use - Shopping malls and boutiques; Hotels; Offices;	
	Showrooms; Restaurants; Hospitals; Schools; Bar Tops, Table Tops.	
	Residential Use – Entrances and hallways; basements;	
	entertainment rooms; bathrooms; kitchens and living rooms;	







No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China