Odorless De Foaming Epoxy Resin Floor Coating Easy To

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-FL2001
Minimum Order Quantity: 300KG

• Price: US\$4.5-6.5/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

Tag Name: Epoxy Flake Floor

Ordinary: 20 Custom Blends Available
 Materials: Epoxy Resin And Hardener
 Key Words: Interior Or Exterior Use

Application: Wood, Brick, Ceramic, Concrete

Mixing Ratio: 2:1 By WeightPot Life: 30 MinutesShelf Life: 12 Months

Highlight: Odorless Epoxy Resin Floor Coating,
 Custom Epoxy Resin Floor Coating

CREKOAT



More Images







Product Description

Epoxy Flakes Flooring Epoxy Resin Floor Coating Highly Durable Easy To Clean

Quick Details Of Epoxy Resin Floor Coating:

From apartment lobbies to retail showrooms, epoxy flakes flooring is an excellent way to give any concrete floor an attractive, durable, and long-lasting appearance. Our mixed color chips are composed of multiple colors, combined using proprietary manufacturing techniques to make each piece unique. Our special formula epoxy resin has been tested with competitors and has been proven to be the strongest, toughest, and most durable epoxy resin directly used in concrete in the industry. Our epoxy resin penetrates into concrete and has excellent lifelong adhesion. Combine our mixed color garage floor epoxy resin flakes with the epoxy resin system for your next installation to achieve truly outstanding results.

Features Of Epoxy Resin Floor Coating:

- 1. Superior Durability & Impact Resistance
- 2. Rapid Return to Service
- 3. Odorless, non-flammable
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Tough, high gloss, water resistant

Advantages Of Epoxy Resin Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Resin Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25ºC	600-800 mPa⋅s	50-150
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	16-24hrs@25°C, 12-15hrs@35°C	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages; Warehouses; Airports and hangars;	
	Commercial Use - Shopping malls and boutiques; Hotels; Offices;	
	Showrooms; Restaurants; Hospitals; Schools; Bar Tops, Table Tops.	
	Residential Use – Entrances and hallways; basements;	
	entertainment rooms; bathrooms; kitchens and living rooms;	







No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China