Resist Wear Tear Epoxy Resin Floor Coating For Broadcast Flake **System**

Basic Information

. Place of Origin: **CHINA** Brand Name: **CREKOAT** · Certification: TDS, MSDS Model Number: CK-FL2001 • Minimum Order Quantity: 300KG

• Price: US\$4.5-6.5/Kg

· Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

. Supply Ability: 1000000 Ton/Year



Product Specification

. Trade Designation: Garage Floor Flakes

• Regular: Residential Concrete Floors Materials: **Epoxy Resin And Hardener** . Key Words: Interior Or Exterior Use

· Application: Wood, Brick, Ceramic, Concrete

Mixing Ratio: 2:1 By Weight Pot Life: 30 Minutes Shelf Life: 12 Months

• Highlight: Resist Wear Epoxy Resin Floor Coating, **Broadcast Flake Epoxy Resin Floor Coating**

CREKOAT



More Images







Product Description

Resist Wear Tear Epoxy Resin Floor Coating For Broadcast Flake System

Quick Details Of Epoxy Resin Floor Coating:

If you are looking for a coating that can resist damage and labeling from chemicals and oils, which can easily be washed away, then this product is perfect for you. It can also resist the wear and tear of chemicals and other factors, such as moving furniture, playing with children, and other activities that can cause scratches or damage the appearance. Our flake system can be installed on uneven surfaces because the texture hides any existing defects, including scratches, debris, and turf. As is well known, this coating can last for 20 years, and if you regularly clean and maintain it, its service life will be longer. If needed, they can be touched to extend their lifespan, making them a sustainable, environmentally friendly, and cost-effective choice.

Features Of Epoxy Resin Floor Coating:

- 1. Delivers an exceptional look to any floor
- 2. Chips available in 4 sizes and over 60 colors
- 3. Odorless, Non-flammable
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Tough, high gloss, water resistant

Advantages Of Epoxy Resin Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Resin Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25ºC	600-800 mPa⋅s	50-150
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	16-24hrs@25°C, 12-15hrs@35°C	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages; Warehouses; Airports and hangars;	
	Commercial Use - Shopping malls and boutiques; Hotels; Offices;	
	Showrooms; Restaurants; Hospitals; Schools; Bar Tops, Table Tops.	
	Residential Use – Entrances and hallways; basements;	
	entertainment rooms; bathrooms; kitchens and living rooms;	







No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China