UV Stable Clear Epoxy Resin Floor Coating Industrial Strength With Flakes

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-FL2001
Minimum Order Quantity: 300KG

• Price: US\$4.5-6.5/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

Product Name: Metallic Flakes For Epoxy
 Customary: Stunning Flake Blends
 Materials: Epoxy Resin And Hardener
 Key Words: Interior Or Exterior Use

Application: Wood, Brick, Ceramic, Concrete

Mixing Ratio: 2:1 By WeightPot Life: 30 MinutesShelf Life: 12 Months

Highlight: Stable Clear Epoxy Resin Floor Coating,
 Industrial Strength Epoxy Resin Floor Coating



More Images







Product Description

UV Stable Clear Epoxy Resin Floor Coating Industrial Strength With Flakes

Quick Details Of Epoxy Resin Floor Coating:

Due to its durability, the epoxy flake coating on concrete floors should be used for at least 5-10 years, and in some cases even longer. Epoxy resin coating has industrial strength and can resist leakage, wear, and various types of damage caused by heavy machinery and pedestrian traffic, making it an ideal choice for many residential and commercial applications. The thickness of the epoxy resin used, the strength of the concrete floor, and the traffic volume in the region are all factors that determine the final lifespan of the epoxy flake coating. Watch our gallery and witness the amazing transformation of epoxy resin coating flakes on concrete floors, and get inspiration for your next residential decoration in a timely manner.

Features Of Epoxy Resin Floor Coating:

- 1. Unique bespoke design
- 2. UV Stable system
- 3. Odorless, non-flammable
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Tough, high gloss, water resistant

Advantages Of Epoxy Resin Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Resin Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa⋅s	50-150
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	16-24hrs@25ºC, 12-15hrs@35ºC	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages; Warehouses; Airports and hangars;	
	Commercial Use - Shopping malls and boutiques; Hotels; Offices;	
	Showrooms; Restaurants; Hospitals; Schools; Bar Tops, Table Tops.	
	Residential Use – Entrances and hallways; basements;	
	entertainment rooms; bathrooms; kitchens and living rooms;	







No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China