Flake Broadcast System Epoxy Resin Floor Coating Standard Solid Colors Topcoat

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 300KG
- Price:

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

- · Packaging Details:
- Delivery Time:
- US\$4.5-6.5/Kg Bottle/Carton/Wooden Box 3-7 Working days

CHINA

CREKOAT

TDS, MSDS

CK-FL2001

- Payment Terms:
 - T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year

CREKOAT



Product Specification

- Official Designation:
- Exemplary:
- Materials:
- . Key Words:
- Application:
- Mixing Ratio:
- Pot Life:
- Shelf Life:
- Highlight:

- Epoxy Flake Garage Floor High Quality Professional Finish
- Epoxy Resin And Hardener
- Interior Or Exterior Use
- Wood, Brick, Ceramic, Concrete
 - 2:1 By Weight
 - 30 Minutes
 - 12 Months
 - Flake Broadcast Epoxy Resin Floor Coating, Standard Solid Epoxy Resin Floor Coating

CREKOAT



More Images







Flake Broadcast System Epoxy Resin Floor Coating Standard Solid Colors Topcoat

Quick Details Of Epoxy Resin Floor Coating:

The adhesive flake broadcast system is a decorative seamless epoxy resin flooring system that broadcast vinyl chips. Full flakes broadcast comes with standard color chips and patterns (see color cards). Custom blends can be created on-site using standard solid colors. The topcoat fixes the vinyl chip in place. One to two coats of topcoat are used to secure vinyl chips. A layer of epoxy or carbamate locking coating is more economical, leaving an aggressive anti slip coating, but more difficult to clean. Two coats of topcoat will make the system smoother, providing a floor with less resistance but easier to clean. Our Flake Broadcast contains antimicrobial agents that prevent the growth of algae, bacteria, fungi, molds, molds, yeast, and more.

Features Of Epoxy Resin Floor Coating:

- 1. Unique bespoke design
- 2. UV Stable system
- 3. Odorless, non-flammable
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Tough, high gloss, water resistant

Advantages Of Epoxy Resin Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Resin Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25ºC	600-800 mPa·s	50-150
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	16-24hrs@25°C, 12-15hrs@35°C	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages; Warehouses; Airports and hangars;	
	Commercial Use - Shopping malls and boutiques; Hotels; Offices;	
	Showrooms; Restaurants; Hospitals; Schools; Bar Tops, Table Tops.	
	Residential Use – Entrances and hallways; basements;	
	entertainment rooms; bathrooms; kitchens and living rooms;	



No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China