# Polymer Epoxy Resin Floor Coating With Decorative Vinyl Colored **Flakes**

### **Basic Information**

. Place of Origin: **CHINA** . Brand Name: **CREKOAT** · Certification: TDS, MSDS Model Number: CK-FL2001 Minimum Order Quantity: 300KG

• Price: US\$4.5-6.5/Kg

Bottle/Carton/Wooden Box Packaging Details:

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

. Supply Ability: 1000000 Ton/Year



## **Product Specification**

Formal Name: Full Flake Epoxy Floor Quintessential: Customize Your Floor · Materials: Epoxy Resin And Hardener . Key Words: Interior Or Exterior Use

· Application: Wood, Brick, Ceramic, Concrete

Mixing Ratio: 2:1 By Weight Pot Life: 30 Minutes Shelf Life: 12 Months

• Highlight: Polymer Epoxy Resin Floor Coating,

Colored Flakes Epoxy Resin Floor Coating



CREKOAT

### More Images







#### **Product Description**

#### Polymer Epoxy Resin Floor Coating With Decorative Vinyl Colored Flakes

#### **Quick Details Of Epoxy Resin Floor Coating:**

If you want to increase the value of your home, improve the durability of the flooring, and beautify your space, you can achieve a dramatic transformation with epoxy flake coating. Epoxy resin flakes are suitable for garages, commercial kitchens, and any surfaces that require wear resistance. The official name is "decorative vinyl colored flakes". Each irregular flake is about 4-5mm thick and is made of polymer coating aggregate composed of vinyl and acrylic resin. The resulting appearance is similar to granite. There are other ways to make thin slices. There are sawdust, metallic flakes, and very commonly used quartz flakes on the market. These different types of flakes have unique uses and are most suitable for special environments.

#### **Features Of Epoxy Resin Floor Coating:**

- 1. Increase durability
- 2. Cover-up flaws
- 3. Odorless, non-flammable
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Tough, high gloss, water resistant

#### **Advantages Of Epoxy Resin Floor Coating:**

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

#### **Product Descriptions Of Epoxy Resin Floor Coating:**

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa⋅s	50-150
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	16-24hrs@25ºC, 12-15hrs@35ºC	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages; Warehouses; Airports and hangars;	
	Commercial Use - Shopping malls and boutiques; Hotels; Offices;	
	Showrooms; Restaurants; Hospitals; Schools; Bar Tops, Table Tops.	
	Residential Use – Entrances and hallways; basements;	
	entertainment rooms; bathrooms; kitchens and living rooms;	







No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China