



Larger Flakes Epoxy Resin Floor Coating Seamless Chip Non Flammable

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-FL2001
- Minimum Order Quantity: 300KG
- Price: US\$4.5-6.5/Kg
- Packaging Details: Bottle/Cartron/Wooden Box
- Delivery Time: 3-7 Working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year



Product Specification

- Official Recognition: Epoxy Chip Flooring
- Natural: Gloss, Satin Or Matte Finish
- Materials: Epoxy Resin And Hardener
- Key Words: Interior Or Exterior Use
- Application: Wood, Brick, Ceramic, Concrete
- Mixing Ratio: 2:1 By Weight
- Pot Life: 30 Minutes
- Shelf Life: 12 Months
- Highlight: **Larger Flakes Epoxy Resin Floor Coating ,
Seamless Chip Epoxy Resin Floor Coating ,
Non Flammable Epoxy Resin Floor Coating**



More Images



Product Description

Larger Flakes Epoxy Resin Floor Coating Seamless Chip Applications

Quick Details Of Epoxy Resin Floor Coating:

Looking for a way to hide splices or cracks in concrete? If you use epoxy resin alone, you will not be able to cover up these defects. But after adding flake chips, these defects will be hidden. Epoxy resin flakes come in hundreds of colors. Usually, you will use a mixture of three colors to achieve the ideal balance of contrast. You can choose from existing color combinations or design a completely personalized look yourself. You can also decide the size of the flakes. They range from around 1/32 inch to 1 inch. Larger flakes are more effective in creating a flat and uniform appearance than smaller flakes.

Features Of Epoxy Resin Floor Coating:

1. Completely smooth surface
2. Seamless chip applications
3. Odorless, non-flammable
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Tough, high gloss, water resistant

Advantages Of Epoxy Resin Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Resin Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa.s	50-150
Density, g/cm ³	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	16-24hrs@25°C, 12-15hrs@35°C 24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages; Warehouses; Airports and hangars; Commercial Use - Shopping malls and boutiques; Hotels; Offices; Showrooms; Restaurants; Hospitals; Schools; Bar Tops, Table Tops. Residential Use – Entrances and hallways; basements; entertainment rooms; bathrooms; kitchens and living rooms;	



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

