# 5mm Vinyl Flakes Epoxy Resin Floor Coating Provide Durability Impact Resistance

## **Basic Information**

. Place of Origin: **CHINA** . Brand Name: **CREKOAT** TDS, MSDS · Certification: CK-FL2001 Model Number: Minimum Order Quantity: 300KG

• Price: US\$4.5-6.5/Kg

Bottle/Carton/Wooden Box Packaging Details:

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

. Supply Ability: 1000000 Ton/Year



# **Product Specification**

. Regular Resignation: Mica Flakes For Epoxy

Symbolic: Improve Safety

Materials: Epoxy Resin And Hardener Interior Or Exterior Use . Key Words:

· Application: Wood, Brick, Ceramic, Concrete

Mixing Ratio: 2:1 By Weight Pot Life: 30 Minutes Shelf Life: 12 Months

• Highlight: 5mm Epoxy Resin Floor Coating,

Impact Resistance Epoxy Resin Floor Coating



# More Images







### **Product Description**

## 5mm Vinyl Flakes Epoxy Resin Floor Coating Provide Durability Impact Resistance

#### **Quick Details Of Epoxy Resin Floor Coating:**

Apply flakes with the maximum coverage on the floor, with a thickness of approximately 5 millimeters. Although epoxy flakes are sturdy, they also have enough elasticity to provide impact resistance. Epoxy flake coating will help buffer concrete and improve its durability. Adding flakes can increase traction and reduce the likelihood of slipping and falling. Cleaning or mopping epoxy flakes flooring is fast and simple, so you won't spend a lot of time or effort maintaining the cleanliness of the garage floor. In addition, you don't need to worry about sunlight shining on the floor, as vinyl chips are stable under ultraviolet radiation. Although the surface should be very wear-resistant, in the end, you may find that it has lost some luster. Repairing it is as simple as putting on a new top.

## **Features Of Epoxy Resin Floor Coating:**

- 1. Easy to maintain
- 2. Vinyl flakes help to dampen sound
- 3. Odorless, non-flammable
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Tough, high gloss, water resistant

#### **Advantages Of Epoxy Resin Floor Coating:**

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

#### **Product Descriptions Of Epoxy Resin Floor Coating:**

lka-ma	Frank Dasin(A)	Handanan(D)
Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25ºC	600-800 mPa⋅s	50-150
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25ºC	
Curing Time	16-24hrs@25°C, 12-15hrs@35°C	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages; Warehouses; Airports and hangars;	
	Commercial Use - Shopping malls and boutiques; Hotels; Offices;	
	Showrooms; Restaurants; Hospitals; Schools; Bar Tops, Table Tops.	
	Residential Use – Entrances and hallways; basements;	
	entertainment rooms; bathrooms; kitchens and living rooms;	







No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China