



Transparent Topcoat Epoxy Resin Floor Coating Broadcasted With Chip Flakes

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-FL2001
- Minimum Order Quantity: 300KG
- Price: US\$4.5-6.5/Kg
- Packaging Details: Bottle/Carton/Wooden Box
- Delivery Time: 3-7 Working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year



Product Specification

- Valid Designation: Full Broadcast Epoxy Floor
- General: Extreme Durability
- Materials: Epoxy Resin And Hardener
- Key Words: Interior Or Exterior Use
- Application: Wood, Brick, Ceramic, Concrete
- Mixing Ratio: 2:1 By Weight
- Pot Life: 30 Minutes
- Shelf Life: 12 Months
- Highlight: **Transparent Topcoat Epoxy Resin Floor Coating**
, Chip Flakes Epoxy Resin Floor Coating



More Images



Product Description

Transparent Topcoat Epoxy Resin Floor Coating Broadcasted With Chip Flakes

Quick Details Of Epoxy Resin Floor Coating:

Now you know how to choose an epoxy resin chip flakes, but how does the installation process proceed? 1. Use epoxy resin flakes after the basecoat. 2. The flakes must be broadcasted throughout the entire floor until a malfunction occurs (which means they are not sticking to the epoxy resin). 3. Scrape off the flakes and add more flakes to fill any gaps. 4. Apply a layer of transparent topcoat. This process may increase the epoxy resin floor coating process by one day or even longer, depending on the size of the floor. Asking professional help can save time and effort, and also ensure a smooth, uniform, and durable application.

Features Of Epoxy Resin Floor Coating:

1. Easy to maintain
2. Vinyl flakes help to dampen sound
3. Odorless, non-flammable
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Tough, high gloss, water resistant

Advantages Of Epoxy Resin Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Resin Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa.s	50-150
Density, g/cm ³	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	16-24hrs@25°C, 12-15hrs@35°C 24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages; Warehouses; Airports and hangars; Commercial Use - Shopping malls and boutiques; Hotels; Offices; Showrooms; Restaurants; Hospitals; Schools; Bar Tops, Table Tops. Residential Use – Entrances and hallways; basements; entertainment rooms; bathrooms; kitchens and living rooms;	



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

