

## 100% Solid Polyaspartic Flake Epoxy Resin Floor Coating Terrazzo Smooth Surface

Our Product Introduction

for more products please visit us on [epoxyresinfloorcoating.com](http://epoxyresinfloorcoating.com)

### Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-FL2001
- Minimum Order Quantity: 300KG
- Price: US\$4.5-6.5/Kg
- Packaging Details: Bottle/Cartron/Wooden Box
- Delivery Time: 3-7 Working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year




### Product Specification

- Formal Identification: Concrete Flakes
- Traditional: Polyaspartic And Epoxy Flooring
- Materials: Epoxy Resin And Hardener
- Key Words: Interior Or Exterior Use
- Application: Wood, Brick, Ceramic, Concrete
- Mixing Ratio: 2:1 By Weight
- Pot Life: 30 Minutes
- Shelf Life: 12 Months
- Highlight: Polyaspartic Flake Epoxy Resin Floor Coating, Smooth Surface Epoxy Resin Floor Coating



### More Images



## Product Description

### 100% Solid Polyaspartic Flake Epoxy Resin Floor Coating Terrazzo Smooth Surface

#### Quick Details Of Epoxy Resin Floor Coating:

The chip and flake system combines high-quality mixed vinyl flakes with epoxy resin and polyaspartic coatings to create a functional and aesthetically pleasing flooring. Epoxy flake floor coating is the ideal choice for all types of environments, providing customized finishes that are suitable for any space. Seamless chip applications have a lightly textured or completely smooth surface that is easy to clean, while also exhibiting excellent wear resistance and long-term wear resistance. Owners can choose from various debris mixtures, including simulated terrazzo floor finishes. This highly economical alternative provides the same appearance and feel as terrazzo at a very low cost. The simulated terrazzo system includes a specialized chip mixture and an additional resin matrix 100% solid grouting coating composed of our Clear Epoxy. Chip systems typically use our high-performance polyaspartic topcoat. The final result is a smooth, easy to maintain floor that performs well in busy traffic environments.

#### Features Of Epoxy Resin Floor Coating:

1. Decorative appearance
2. Completely smooth surface, seamless
3. Odorless, non-flammable
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Tough, high gloss, water resistant

#### Advantages Of Epoxy Resin Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

#### Product Descriptions Of Epoxy Resin Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa·s	50-150
Density, g/cm <sup>3</sup>	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	16-24hrs@25°C, 12-15hrs@35°C 24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages; Warehouses; Airports and hangars; Commercial Use - Shopping malls and boutiques; Hotels; Offices; Showrooms; Restaurants; Hospitals; Schools; Bar Tops, Table Tops. Residential Use – Entrances and hallways; basements; entertainment rooms; bathrooms; kitchens and living rooms;	



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

