

Vinyl Flake Broadcast Epoxy Resin Floor Coating Polyaspartic Topcoat

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-FL2001
- Minimum Order Quantity: 300KG
- Price: US\$4.5-6.5/Kg
- Packaging Details: Bottle/Cartron/Wooden Box
- Delivery Time: 3-7 Working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year



Product Specification

- Formal Recognition: Color Flakes For Epoxy Floor
- Distinguishing: Excellent Resistance To Abrasion
- Materials: Epoxy Resin And Hardener
- Key Words: Interior Or Exterior Use
- Application: Wood, Brick, Ceramic, Concrete
- Mixing Ratio: 2:1 By Weight
- Pot Life: 30 Minutes
- Shelf Life: 12 Months
- Highlight: Vinyl Flake Epoxy Resin Floor Coating, Polyaspartic Epoxy Resin Floor Coating



More Images



Product Description

Vinyl Flake Broadcast Epoxy Resin Floor Coating Polyaspartic Topcoat

Quick Details Of Epoxy Resin Floor Coating:

Seamless chip systems can be built in various ways to meet environmental requirements and installation parameters. Generally speaking, these systems include primer, vinyl flake broadcast, grouting coating, and topcoat. Primers can be composed of various epoxy resins, polyurethane concrete, or polyaspartic coating materials, depending on the specific requirements of the project. These products can be replaced to address situations such as high moisture transfer rates in concrete, existing substrate conditions, and project recovery requirements. According to the preferences of the owner or designee, modifications can be made to the grouting layer and topcoat to increase or decrease texture. In addition, topcoat can also increase adhesion and have the ability to provide a glossy, satin or matte finish.

Features Of Epoxy Resin Floor Coating:

1. Decorative appearance
2. Completely smooth surface, seamless
3. Odorless, non-flammable
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Tough, high gloss, water resistant

Advantages Of Epoxy Resin Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Resin Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa·s	50-150
Density, g/cm ³	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	16-24hrs@25°C, 12-15hrs@35°C 24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages; Warehouses; Airports and hangars; Commercial Use - Shopping malls and boutiques; Hotels; Offices; Showrooms; Restaurants; Hospitals; Schools; Bar Tops, Table Tops. Residential Use – Entrances and hallways; basements; entertainment rooms; bathrooms; kitchens and living rooms;	



