Colored Flakes Epoxy Resin Floor Coating High Gloss Grey Finishes

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-FL2001
Minimum Order Quantity: 300KG

• Price: US\$4.5-6.5/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

• Formally Recognizing: Glitter Flakes For Epoxy Floors

Mainstream: Epoxy Flake Coating
 Materials: Epoxy Resin And Hardener
 Key Words: Interior Or Exterior Use

Application: Wood, Brick, Ceramic, Concrete

Mixing Ratio: 2:1 By WeightPot Life: 30 MinutesShelf Life: 12 Months

• Highlight: Colored Flakes Epoxy Resin Floor Coating,

Epoxy Resin Floor Coating High Gloss



More Images







Product Description

Colored Flakes Epoxy Resin Floor Coating High Gloss Grey Finishes

Quick Details Of Epoxy Resin Floor Coating:

When choosing an epoxy floor coating, you need to choose a color. If you want a classic appearance, white or grey epoxy resin is a good choice. You can find almost any color of epoxy resin to get more unique things. The final consideration is the glossiness you want. High gloss finishes are easy to clean, but are more prone to defects. Low gloss or matte finishes are more tolerant, but may require more frequent cleaning to maintain their appearance. After proper maintenance and upkeep, epoxy flake flooring can be used for many years. Colored flakes help conceal any slight scratches or wear, and diamond ground surfaces will maintain a good appearance in the coming years. Regular cleaning and mopping can help keep the floor clean, while occasional deep cleaning can help remove accumulated dirt.

Features Of Epoxy Resin Floor Coating:

- 1. Impenetrable to moisture
- 2. Highly hygienic, glossy finish
- 3. Odorless, non-flammable
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Tough, high gloss, water resistant

Advantages Of Epoxy Resin Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Resin Floor Coating:

lka-ma	Frank Dasin(A)	Handanan(D)
Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25ºC	600-800 mPa⋅s	50-150
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25ºC	
Curing Time	16-24hrs@25°C, 12-15hrs@35°C	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages; Warehouses; Airports and hangars;	
	Commercial Use - Shopping malls and boutiques; Hotels; Offices;	
	Showrooms; Restaurants; Hospitals; Schools; Bar Tops, Table Tops.	
	Residential Use – Entrances and hallways; basements;	
	entertainment rooms; bathrooms; kitchens and living rooms;	







No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China