100% Solid Epoxy Resin Flake Concrete Coating 2 Component Product

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-FL2001
Minimum Order Quantity: 300KG

• Price: US\$4.5-6.5/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

Formal Term: Floor Paint With Flakes

Stock: Black Epoxy Floor With Flakes
 Materials: Epoxy Resin And Hardener
 Key Words: Interior Or Exterior Use

Application: Wood, Brick, Ceramic, Concrete

Mixing Ratio: 2:1 By WeightPot Life: 30 MinutesShelf Life: 12 Months

• Highlight: Solid Epoxy Resin Flake Concrete Coating,

2 Component Resin Flake Concrete Coating



More Images







Product Description

100% Solid Epoxy Resin Flake Concrete Coating Two Component Product

Quick Details Of Flake Concrete Coating:

The rapid curing of epoxy resin is a key component of our flake system, which is a fast curing, VOC compliant, 100% solid, two component product used as a primer and broadcast coating for colored flakes (chips) and other flooring. It has good adhesion and concealment to concrete in single coating applications. It can also withstand moisture emissions of up to 9 pounds (6.9% MC) without the need for barrier coatings in many cases. Adhere to damp or dry concrete and provide sufficient opening time for broadcast into the coating. At the same time, it quickly solidifies for customers, with low odor and zero volatile organic compounds. Our epoxy flake system is a better experience for all participants.

Features Of Flake Concrete Coating:

- 1. High chemical resistance
- 2. Glass like shine, 0 VOC
- 3. Odorless, non-flammable
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Tough, high gloss, water resistant

Advantages Of Flake Concrete Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Flake Concrete Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25ºC	600-800 mPa⋅s	50-150
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	16-24hrs@25°C, 12-15hrs@35°C	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages; Warehouses; Airports and hangars;	
	Commercial Use - Shopping malls and boutiques; Hotels; Offices;	
	Showrooms; Restaurants; Hospitals; Schools; Bar Tops, Table Tops.	
	Residential Use – Entrances and hallways; basements;	
	entertainment rooms; bathrooms; kitchens and living rooms;	







No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China