

TDS Colour Flake Epoxy Resin Floor Coating Liquid Resistant

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-FL2001
- Minimum Order Quantity: 300KG
- Price: US\$4.5-6.5/Kg
- Packaging Details: Bottle/Cartron/Wooden Box
- Delivery Time: 3-7 Working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year




Product Specification

- Dignified Name: Epoxy Chip Garage Floor
- Orthodox: Two Pack Epoxy Resin Systems
- Materials: Epoxy Resin And Hardener
- Key Words: Interior Or Exterior Use
- Application: Wood, Brick, Ceramic, Concrete
- Mixing Ratio: 2:1 By Weight
- Pot Life: 30 Minutes
- Shelf Life: 12 Months
- Highlight: Colour Flake Epoxy Resin Floor Coating, TDS Epoxy Resin Floor Coating



More Images



Product Description

Epoxy Colour Flake Coating Epoxy Resin Flooring Liquid Resistant

Quick Details Of Epoxy Colour Flake Coating:

Most commercial and residential garages have epoxy resin flooring. The main reason for this situation is that the epoxy resin coating on the garage floor is liquid resistant. Therefore, chemical, grease, and oil spills, as well as rain and snow on epoxy resin floors, rarely cause any significant stains or damage. Business and home interiors also make epoxy flooring one of their top choices. Although epoxy flooring in commercial and residential garages has aesthetic appeal, the main focus is on the floor's resistance to liquids, tire marks, and impact. However, when epoxy resin flooring is installed inside a business or home, aesthetic appeal occupies a central position. This is where epoxy flake flooring comes.

Features Of Epoxy Colour Flake Coating:

1. Non-slip epoxy flooring
2. Decorative, hygienic
3. Odorless, non-flammable
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Tough, high gloss, water resistant

Advantages Of Epoxy Colour Flake Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Colour Flake Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa.s	50-150
Density, g/cm ³	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	16-24hrs@25°C, 12-15hrs@35°C 24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages; Warehouses; Airports and hangars; Commercial Use - Shopping malls and boutiques; Hotels; Offices; Showrooms; Restaurants; Hospitals; Schools; Bar Tops, Table Tops. Residential Use – Entrances and hallways; basements; entertainment rooms; bathrooms; kitchens and living rooms;	



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

