Multi Color Epoxy Flake Floor Coating With Water Based Clear Epoxy Resin

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-FL2001
Minimum Order Quantity: 300KG

• Price: US\$4.5-6.5/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

Academic Name: Polyaspartic Flake Floor
 Prevailing: Epoxy Flake Flooring
 Materials: Epoxy Resin And Hardener
 Key Words: Interior Or Exterior Use

Application: Wood, Brick, Ceramic, Concrete

Mixing Ratio: 2:1 By WeightPot Life: 30 MinutesShelf Life: 12 Months

Highlight: Multi Color Epoxy Flake Floor Coating,
 Water Based Epoxy Flake Floor Coating



More Images







Product Description

Multi Colors Epoxy Flake Floor Coating With Water Based Clear Epoxy Resin

Quick Details Of Epoxy Flake Floor Coating:

Epoxy resin flakes, color chips, and color flasks, no matter what they are called, are all color explosions that will definitely turn dull floors into interesting and attractive ones. Vinyl colored flake is a mixture of vinyl resin and acrylic (approximately 4mm thick). When choosing the color of flakes, always consider the color of the basecoat floor. The epoxy resin flake coating should match the color of the basecoat floor. However, if the entire floor needs to be covered with epoxy resin flakes, there is no need for the basecoat floor to match the epoxy resin flakes. Floors can also be covered with lightweight, medium, and heavy-duty epoxy flakes.

Features Of Epoxy Flake Floor Coating:

- 1. Water based epoxy resin
- 2. Available in various colors
- 3. Odorless, non-flammable
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Tough, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa⋅s	50-150
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	16-24hrs@25ºC, 12-15hrs@35ºC	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages; Warehouses; Airports and hangars;	
	Commercial Use - Shopping malls and boutiques; Hotels; Offices;	
	Showrooms; Restaurants; Hospitals; Schools; Bar Tops, Table Tops.	
	Residential Use – Entrances and hallways; basements;	
	entertainment rooms; bathrooms; kitchens and living rooms;	







No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China