

Anti Slip Flake Epoxy Coating Garage Epoxy Resin Flooring With **Flakes**

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 300KG
- Price:
- Packaging Details:
- Delivery Time:
- 3-7 Working days • Payment Terms: T/T, Western Union, MoneyGram

CHINA

CREKOAT

TDS, MSDS

CK-FL2001

US\$4.5-6.5/Kg

1000000 Ton/Year

Bottle/Carton/Wooden Box

• Supply Ability:





Product Specification

- Conventional Name:
- Paradigmatic:
- Materials:
- . Key Words:
- Application:
- Mixing Ratio:
- Pot Life:
- Shelf Life:
- Highlight:

- Garage Paint With Flakes Eco-Friendly
- Epoxy Resin And Hardener
- Interior Or Exterior Use
- Wood, Brick, Ceramic, Concrete
- 2:1 By Weight
- 30 Minutes
- 12 Months
 - Anti Slip Flake Epoxy Coating, Flake Epoxy Coating With Flakes

CREKOAT



More Images







Our Product Introduction

Anti Slip Flake Epoxy Coating Garage Epoxy Resin Flooring With Flakes

Quick Details Of Flake Epoxy Coating:

Garages can also benefit from epoxy flake flooring. Don't you want a practical and very beautiful garage floor? Let's take a look at what epoxy flake flooring can provide. For this reason, epoxy resin flooring with flakes or debris is often chosen. They just look beautiful! The garage is usually considered one of the most important areas in the family, where the whole family gathers to work and play. Therefore, the goal of homeowners is often to make the garage floor look as flashy and gorgeous as possible. Epoxy flake flooring can achieve this - making your garage floor look beautiful. This not only applies to garage and interior decoration. The commercial district is also designed for practicality and aesthetics.

Features Of Flake Epoxy Coating:

- 1. Solvent free, no odor
- 2. Compatible with vehicles
- 3. Odorless, non-flammable
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Tough, high gloss, water resistant

Advantages Of Flake Epoxy Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Flake Epoxy Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25ºC	600-800 mPa·s	50-150
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	16-24hrs@25ºC, 12-15hrs@35ºC	
	24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages; Warehouses; Airports and hangars; Commercial Use - Shopping malls and boutiques; Hotels; Offices; Showrooms; Restaurants; Hospitals; Schools; Bar Tops, Table Tops. Residential Use – Entrances and hallways; basements;	
	entertainment rooms; bathrooms; kitchens and living rooms;	



No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China