

Flake Epoxy Resin Concrete Paint Anti Slip Protection For Garage Flooring

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-FL2001
- Minimum Order Quantity: 300KG
- Price: US\$4.5-6.5/Kg
- Packaging Details: Bottle/Cartron/Wooden Box
- Delivery Time: 3-7 Working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year





Product Specification

- Correct Name: White Epoxy Floor With Flakes
- Plain: Hard Wearing
- Materials: Epoxy Resin And Hardener
- Key Words: Interior Or Exterior Use
- Application: Wood, Brick, Ceramic, Concrete
- Mixing Ratio: 2:1 By Weight
- Pot Life: 30 Minutes
- Shelf Life: 12 Months
- Highlight: Flake Epoxy Resin Concrete Paint, Anti Slip Epoxy Resin Concrete Paint



More Images



Product Description

Epoxy Resin Concrete Flake Paint Anti Slip Protection For Garage Flooring

Quick Details Of Concrete Flake Paint:

Epoxy resin flakes can mask the defects of concrete and epoxy resin floor coatings themselves. The epoxy resin flakes attracted so much attention that the defects on the floor were almost unnoticed. As long as you have enough creativity, you can provide a unique epoxy flake floor for your garage that can be used for a long time. This is a simple process. First, take a look at the theme of your home. Choose a flake flooring design that complements both color and design. If there is a lot of traffic in your garage, choose dark snowflakes. Determine the size of the flakes and the floor area you want to cover. You can also choose to add anti slip protection on epoxy flake flooring.

Features Of Concrete Flake Paint:

1. Seamless high build coating
2. Outstanding adhesion
3. Odorless, non-flammable
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Tough, high gloss, water resistant

Advantages Of Concrete Flake Paint:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Concrete Flake Paint:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa.s	50-150
Density, g/cm ³	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	16-24hrs@25°C, 12-15hrs@35°C 24hrs, Dry Completely	
Thickness	1-3 mm	
Recoat Time	2Hrs	
Shelf Life	12 Months	
Application	Industrial Use - Garages; Warehouses; Airports and hangars; Commercial Use - Shopping malls and boutiques; Hotels; Offices; Showrooms; Restaurants; Hospitals; Schools; Bar Tops, Table Tops. Residential Use – Entrances and hallways; basements; entertainment rooms; bathrooms; kitchens and living rooms;	



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

